



INV-AV131PRO1X4

131 Feet (40M) 1080P@60Hz HDMI 1X4 splitter over Cat6 with IR, with HDMI loop-out on TX, with EDID. Distribute 1 HDMI source to 4 HD displays over network cable simultaneously. Support one HDMI Loop-out. Compatible with CAT6/6a/7 network cables. The transmission distance is 131 Feet (40M) . The Highest resolution is up to 1920x1080@60Hz. Support 20~60Hz IR pass back. Support EDID. Plug and play. Wall-mounted function, easy installation.

Technical	Transmitter	Receiver
Input	HDMI×1 (Type A, 19 pin, female)	
Output	RJ45×4	
Transmission distance	40 meters via CAT6	
Video support	480i@60Hz, 480p@60Hz, 576i@50Hz, 576p@50/60Hz, 1080i@50/60Hz, 1080p@50/60Hz	
Audio format	PCM DTS AC3	
TMDS signal	0.5~1.5Vp-p(TMDS)	
DDC signal	5Vp-p(TTL)	
IR passback function	Support	
IR frequency Range (KHz)	Support 20~60KHz IR frequency devices	
HDMI loopout	Support	
POT (receiver powered from transmitter)	Support	
HDCP	HDCP1.2	
HDMI Distance	1080p: 25 Foot Maximum Distance	
Mechanical		
Housing	Metal enclosure	
Dimensions (L × W× H)	7.5 x 3.8 x .94 in (190×95.5×23.9 mm)	2.8 x 2.6 x .89 in (71.6×66.6×22.6mm)
Fixedness	wall-mounting case with screws	
Power supply	5V/2A 1pcs 5V1A 4pcs	
Power consumption	<15W	
Operation Temperature	32°F ~140°F (0°C ~60°C)	
Storage Temperature	-4°F ~140°F (-20°C ~70°C)	
Relative humidity	20~90%(no condensation)	

Ordering Information
INV-AV131PRO1X4: HDMI Splitter