



## INV-AV393KIT1X4

393 Feet (120m) 1080P@60Hz HDbiT HDMI Splitter  
 1\*4 kits Distribute 1 HDMI source to 4 HDbiT outputs

Technical	
Input	HDMI×1( Type A, 19 pin, female)
Output	HDbiT×4 (RJ45 connector)
HDMI signal	HDMI1.3 Compatibel with HDCP1.4
HDMI Distance	1080p: 25 Foot Maximum Distance
Transport protocol	HDbiT
Working mode	Should work together with HDbiT HDMI Receiver units
Transmission distance	CAT5/80 meters, CAT5e/100meters, CAT6/120 meters (realize by working together with HDbiT transmitter)
Video support	480i@60Hz, 480p@60Hz, 576i@50Hz, 576p@50Hz, 720p@50/60Hz, 1080i@50/60Hz, 1080p@50/60Hz
Audio format	PCM
TMDS signal	0.5~1.5Vp-p (TMDS)
DDC signal	5Vp-p (TTL)
IR passback	Support 20~60KHz IR frequency devices
Mechanical	
Housing	Metal enclosure
Dimensions (L×W×H)	9.9 x 3.8 x .98 in (252 x 97.5 x 25 mm)
Net weight	1.18 lb (535g)
Fixedness	wall-mounting case with screws
Power supply	5V/2A
Power consumption	<10W
Operation tempaure	32°F ~140°F (0°C ~60°C)
Protection	Lightning Protection
	Surge Protection
	ESD protection
Storage temperature	-4°F ~140°F (-20°C ~70°C)
Relative humidity	20~90% (no condensation)

### Ordering Information

**INV-AV393KIT1X4:** HDMI Splitter