



## CON-MINIHUB16

15.6" FHD LCD Screen Desktop meeting Terminal, PCAP Touch, support up to 10 points touch, 48 megapixel FHD camera, FOV 90°, Built-in six-array microphone, Built-in stereo speaker, Anti-glared glass

### Features

- 15.6" FHD LCD Screen
- PCAP Touch, support up to 10 points touch
- 48 megapixel FHD camera, FOV 90°
- Built-in six-array microphone
- Built-in stereo speakers
- Anti-glared glass
- Android 8.00

Display	
Size	15.6"
Type	ADS
Response Time	30ms
Aspect Ratio	0.672916667
Display Area	344.16 (H) × 193.59 (V) mm
Resolution	1920 (H) × 1080 (V)
Pixel Pitch	0.17925×0.17925 mm
Refreshing Frequency	60Hz
Display Color	262K(6bit)
NTSC(Typ)	0.45
Contrast Ratio(Typ)	33.33402778
Viewing Angle	170°(H/V)
Back Light Unit	ELED
Brightness with glass(Typ)	200cd/m2
Life Time	≥30000 hours
Android System	
System Version	Android 8.0
CPU	A73*2+A53*2
GPU	Mali-G51*4
RAM	4G
ROM	16G
Touch System	
Sensing Type	Capacitance recognition
Touch Point	10 points touch
Touch Tool	Capacitance pen; finger
Minimum object size	6mm
Accuracy	±2mm
Writing Height	0

### Ordering Information

**CON-MINIHUB16:** 15.6" FHD LCD Screen Desktop meeting Terminal

Audio	
Sound Chanel	1
Output Power	1×8W
Microphone	
Number of Arrays	4
Voice Pick-up Distance	0~6m
Camera	
Number of Camera	1
Pixel	48 megapixel
Position	Top
Wi-Fi	
Version	802.11 a/b/g/n/ac
Frequency	2.4GHz/5GHz
Working Distance	0~10m
Power	
Power Requirements	12V DC 3.0A
Overall Power	36W
Standby	≤0.5W
I/O Port	
HDMI OUT	1
USB2.0	2
USB3.0	1
USB Type-C	1 (for Debug)
RJ45	1
Earphone	1
DC 2.0	1
Physical Dimensions	
Dimension (LxHxD)	14 x 11 x 2 in (362.2×295.1×42.9 mm)
Package Dimension (LxWxH)	16 x 3 x 14 in (425×100×363mm)
Net Weight	3 lbs (1.74kg)
Gross Weight	5 lbs (2.55kg)
Accessories	
Power Cord	x 1
Documents	
User Manual	x 1
Warranty Card	x 1
Environmental Conditions	
Working Temperature	32°F - 104°F (0°C ~40°C)
Working Humidity	10%~90%RH
Storage Temperature	-4°F - 140°F (-20°C ~60°C)
Storage Humidity	10%~90%RH
Working Height	Less than 5000m