



ELEV-C5LIRN

5-2 Megapixel Field Selectable TVI/AHD/CVI/CVBS, Outdoor Low Profile, 30' IR Range, True WDR, 12VDC

Features

- 5-2 Megapixel Field Selectable**
- All-in-One Technology (TVI/AHD/CVI/Analog 960h)
- Fixed Lens
- True Day/Night
- True WDR
- 30' Smart IR Range
- Up The Cable (UTC) Function
- IP66 Weather Resistant
- 12VDC Only Operation
- Through InVid Tech DVR:
Free App, CMS & MAC Client

Camera	
Filter	Removable IR Cut Filter
Image Sensor	1/2.8" 5Mega-pixel Sony CMOS
Pixels	2592(H)*1944(V)
Video Output	TVI:5MP 20/12.5 FPS, 4MP/2MP 30/25 FPS AHD:5MP 20/12.5 FPS, 4 MP / 2MP 30/25 FPS CVI:4MP 30/25 FPS, 2 MP 30/25 FPS CVBS"
Video Output By Default	TVI: 5MP @ 20 FPS AHD:2MP @ 30 FPS CVI: 2MP @ 30 FPS CVBS"
Min Illumination	0Lux(10PCs led ON)
Vertical Frequency	NTSC:60Hz PAL:50Hz
IR Range	30 Feet
S/N Ratio	≥54DB
Lens	Fixed 2.8mm IR Lens, Horizontal Angle 105 Degree
White Balance	ATW (PRO default), Gray World Optional
BackLight Compensation	OFF (Default)
Day&Night	Default EXT (B/W, Color, AUTO Optional)
OSD	Support
AUTO Gain Control	ON (Default)
3DNR	AUTO
True WDR	Default OFF (≥ 120DB)
Auto Exposure Mode	Default GLOBAL
Defog	OFF/ON
General	
Power Supply	DC12V ±10%
IP Rating	IP66
Dimension	3.87"×3.87×2.46" (98.4×98.4×62.5mm)
Weight	.73lbs (330g)
Storage Temperature	-22 °F +149 °F (-30°C+65°C)
Operating Temperature	-22 °F+122 °F (-30°C+50°C)

Ordering Information

ELEV-C5LIRN: 5 Megapixel Low Profile, Fixed 2.8mm

**Scale down to other resolutions via camera dip switches & OSD

InVid Tech, reserves the right to make changes to improve our products at any time without notice; we are not responsible for misprints.