



ELEV-P4SMOKENH

4 Megapixel IP Plug & Play, Indoor Covert Smoke Detector Housing, Fixed Lens, WDR, Audio Input, 12VDC/PoE

Features

- 4 Megapixel Resolution
- Fixed Lens
- H.264/H.264+/H.265/H.265+
- 30 FPS Recording and Live
- WDR
- Audio Input
- Indoor Only
- 12VDC/PoE
- Free iOS & Android Apps for Smart Phones & Tablets
- Free Central Management Software (CMS) for PC/MAC

Camera	ELEV-P4SMOKENH
Image Sensor	1/2.7" Progressive Scan CMOS Sensor
Min. Illumination	0.008 lux (Color)
Illumination Distance	N/A
Smart IR	N/A
Pan/Tilt/Rotation Range	Pan: 0° ~ 0° Tilt: 0° ~ 0° Rotation: 0°
Lens	
Focal Length	2.8 mm
Aperture	F2.0
FOV	2.8 mm @ F2.0 Horizontal FOV: 92°, Vertical FOV: 52°, Diagonal FOV: 107°
Lens Mount	M12
Compression Standard	
Video Compression	H.264/H.264+/H.265/H.265+
H.264 Codec Profile	Base/Main/High profile
H.265 Codec Profile	Main profile
Video Bit Rate	11 Kbps ~ 10 Mbps
Triple Streams	Support
Audio Compression	G.711A/G.711U
Audio Bit Rate	64 Kbps
Image	
Max. Image Resolution	4MP (2688 × 1520)

Main Stream	50Hz: 25fps 4MP (2688 × 1520) 25fps 3MP (2304×1296) 25fps 1080P (1920 × 1080)
Sub Stream	60Hz: 30fps 4MP (2688 × 1520) 30fps 3MP (2304×1296) 30fps 1080P (1920 × 1080)
Third Stream	50Hz: 25fps 720P (1280 × 720) 25fps D1 (704 × 576) , 25fps CIF (352 × 288) 25fps MJPEG
Image Setting	Brightness/Contrast/Saturation/Hue/Sharpness
Shutter Time	Auto/Manual, 1/3 ~ 1/100000s
Day/Night	N/A
Wide Dynamic Range	WDR
Digital Noise Reduction	2D/3D DNR
BLC	Support
HLC	Support
ROI	Support
Rotate	Support
Smart Feature	
Basic Event	Motion detection (support alarm triggering by specified target types (human body, on Protect Series)), Video Shelter
Smart Event	N/A
Face Detection	N/A
Network	
Network Storage	N/A
Protocols	TCP/IP, ICMP, HTTP, HTTPS, DHCP, DNS, DDNS, RTP, RTSP, RTCP, NTP, IGMP, UPnP, SMTP, UPnP-TM, P2P, Bonjour, IPV6
System Compatibility	Onvif (Profile S,G,T), CGI
Security	User authentication,IP address filtering,Video mask
User	Up to 10 user
Web Browsers	IE, edge, Firefox, Chrome
Mobile Surveillance	iPhone, iPad, Android, CMS, WEB (InVid Protect)
Interface	
Communication Interface	1 RJ45 10M / 100M Ethernet Port
On-board Storage	N/A
MIC	N/A
Speaker	N/A
Audio I/O	1/0
Alarm I/O	N/A
Reset Button	N/A
General	
Operating Conditions	14°F ~ 113°F (-10°C ~ 45°C) Humidity 95% or less (non-condensing)
Power Supply	DC12V ± 10%
POE	PoE (802.3 af)
Power Consumption	MAX. 2.7 W
Protection Level	N/A
Material	Plastic
Dimensions	4.72" × 2.28" (120 x 58 mm)
Gross Weight	0.70 lb (320g)

Ordering Information

ELEV-P4SMOKENH: 4 Megapixel Smoke Detector, 2.8mm Enclosure & Camera Only: Non-Operational Smoke Detector