



ELEV-P5DRIRLC

5 Megapixel IP Plug & Play, Outdoor Dome, 82' IR Range, PoE/DC 12V

Features

- 5 Megapixel Resolution
- Fixed Lens
- True Day/Night with IR Range up to 82'
- Smart IRs
- H.265/H.265+/H.264/H.264+ Compression
- D-WDR
- Smart Analytics
- IP66 Weather Resistant
- IK10 Vandal Resistant
- 12VDC/PoE Operation
- Free iOS & Android Apps for Smart Phones & Tablets
- Free Central Management Software (CMS)
- Free MAC Client

| | |
|-------------------------|---|
| Camera | ELEV-P5DRIR28LC |
| Sensor+DSP | K03+HI3516D |
| Image Sensor | 1/2.5" Progressive scan CMOS |
| Min. Illumination | 0.01lux(Color), 0lux(IR on) |
| Shutter Time | Auto/Manual, 1/3~1/10000s |
| Slow Shutter | Support |
| Lens | 2.8 mm@F1.8: horizontal FOV: 102°, vertical FOV:74° |
| Lens Mount | M12 |
| Day/Night | IR cut filter with auto switch |
| Wide Dynamic Range | DWDR |
| Digital noise reduction | 2D/3D DNR |
| IR | 14µx18pcs SMD LED |
| Max. IR LEDs Length | 82 ft |
| Smart IR | Support |
| Compression Standard | |
| Video Compression | H.264/H.264+/H.265/H.265+ |
| H.264 Codec profile | Base/Main/High profile |
| H.265 Codec profile | Main profile |
| Video Bit Rate | 11 Kbps~8 Mbps |
| Triple Streams | Support |
| Image | |
| Max.resolution | 5MP (2592 x 1944)(default 15fps) |
| Frame Rate | <p>Main Stream: 50Hz:20fps 5MP(2592 x 1944) 25fps 4MP(2560 x 1440),23fps 4MP(2304 x 1728) 25fps 3MP(2048 x 1536),25fps 1080P(1920 x 1080) 25fps 960P(1280 x 960), 60Hz:20fps 5MP(2592 x 1944) 28fps 4MP(2560 x 1440),26fps 4MP(2304 x 1728) 30fps 3MP(2048 x 1536),30fps 1080P(1920 x 1080) 30fps 960P(1280 x 960),30fps 720P(1280 x 720)*</p> <p>Sub Stream: 50Hz:25fps 720P(1280 x 720) 25fps D1(704 x 576),25fps CIF(352 x 288) 60Hz:30fps 720P(1280 x 720) 30fps D1(704 x 480),30fps CIF(352 x 240)*</p> <p>Mobile Stream: 50Hz:25fps CIF(352 x 288) 60Hz:30fps CIF(352 x 240)*</p> |
| Image Setting | Brightness/Contrast/Saturation/Hue/Sharpness |
| BLC | On/Off, zone configurable |
| HLC | Support |
| ROI | Support |
| Defog | Support |
| Network | |
| Network Storage | NAS(NFS/CIFS) |
| Protocols | TCP/IP,ICMP,HTTP,HTTPS,FTP,DHCP,DNS,DDNS,RTP,RTSP, RTCP,NTP,IGMP,UPnP,SMTP,UPnP-TM,P2P,Bonjour* |
| Event | Motion Detection, Video Shelter |
| Smart Functions | Area Intrusion, Line crossing, Object Missing, Unattended Object, Fast Moving |
| System compatibility | CGI |
| Security | User authentication,IP address filtering,Video mask |
| Mobile Surveillance | iPhone, iPad,Android devices |
| Interface | |
| Communication interface | 1 RJ45 10M / 100M Ethernet Port |
| General | |
| Operating Conditions | -30 °C ~ 60 °C (-22 °F ~ 140 °F) Humidity 95% or less (non-condensing) * |
| Power Supply | DC12V ± 10% |
| POE Supply | PoE (802.3af) |
| Power Consumption | Max. 7W |
| Weather Proof | IP66 |
| Dimensions | 67.5x57.5x152mm |
| Weight | 365g |
| Dimensions | ø4.48 x 3.54" (ø114 x 90(H) mm) |
| Weight | 1.1 lbs (500g) |

Ordering Information

ELEV-P5DRIR28LC: 5 Megapixel Dome, 2.8mm