



## ELEV-P4MIBP37

4 Megapixel IP Plug & Play, Indoor Metal Case Camera, WDR, PoE/DC12V

### Features

- 4 Megapixel (2560 x 1440) Resolution
- Fixed Lens
- H.265/H.265+/H.264/H.264+ Compression
- Day/Night
- True WDR 120dB
- Audio Input/Output
- Indoor Only
- 12VDC/PoE Operation
- Smart Analytics
- Free iOS & Android Apps for Smart Phones & Tablets
- Free Central Management Software (CMS) to manage multiple units & sites from a single platform
- Free MAC client software available to manage your system from your Apple computer

Camera	ELEV-P4MIBP37
Sensor+DSP	OV4689+Hi3516D
Image Sensor	1/3" Progressive scan CMOS Sensor
Min. Illumination	0.01lux(Color)
Lens Mount	M12
Lens	3.7 mm Pinhole Lens
View Angle	Horizontal FOV: 75°, Vertical FOV:56°
Shutter Time	Auto/Manual, 1/3~1/10000s
Day/Night	IR filter with auto switch
Wide Dynamic Range	WDR 120dB
Digital noise reduction	2D/3D DNR
Compression Standard	
Video Compression	H.264/H.264+/H.265/H.265+
H.264 Codec profile	Base/Main/High profile
H.265 Codec profile	Main profile
Video Bit Rate	11 Kbps~9 Mbps
Triple Streams	Support
Audio Compression	G.711A
Audio Bit Rate	64 Kbps
Image	
Max. Image Resolution	4MP(2560 × 1440)
Frame Rate	50Hz 25fps 4MP(2560 × 1440),23fps 4MP(2304 × 1728) 25fps 3MP(2048 × 1536),25fps 1080P(1920 × 1080) 25fps 960P(1280 × 960),25fps 720P(1280 × 720) 60Hz 28fps 4MP(2560 × 1440),26fps 4MP(2304 × 1728) 30fps 3MP(2048 × 1536),30fps 1080P(1920 × 1080) 30fps 960P(1280 × 960),30fps 720P(1280 × 720)
Sub Stream	50Hz:25fps D1(704 × 576),25fps CIF(352 × 288) 60Hz:30fps D1(704 × 480),30fps CIF(352 × 240)
Third Stream	50Hz:25fps CIF(352 × 288) 60Hz:30fps CIF(352 × 240)
Image Setting	Brightness/Contrast/Saturation/Hue/Sharpness
BLC	Support
HLC	Support
ROI	Support
Defog	Support
Network	
Network Storage	NAS(NFS/CIFS)
Protocols	TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, NTP, IGMP, UPnP, SMTP, UPnP-TM, P2P, Bonjour
Event	Motion Detection, Video Shelter
Smart Functions	Area Intrusion, Line crossing, Object Missing, Unattended Object, Fast Moving
System compatibility	CGI
Security	User authentication,IP address filtering,Tampering
Mobile Surveillance	iPhone, iPad,Android devices
Interface	
Communication interface	1 RJ45 10M / 100M Ethernet Port
Audio I/O	1/1
Reset button	Support
General	
Operating Conditions	-22°F ~ 140°F (-30°C ~ 60°C) Humidity 95% or less (non-condensing)
Power Supply	DC12V ± 10%
POE Supply	PoE (802.3af) (External)
Power Consumption	MAX. 6W
Dimensions	ø 1.43" x 1.43" (ø 36.51 x 36.51mm)
Weight	0.66lbs (300g)

### Ordering Information

**ELEV-P4MIBP37:** 4 Megapixel Metal Case Camera, 3.7mm, Black