



ELEV-P4SMOKE

4 Megapixel IP Plug & Play, Indoor Covert Smoke Detector Housing, WDR, PoE/DC12V

Features

- 4 Megapixel (2560 x 1440) Resolution
- Fixed Lens
- H.265/H.265+/H.264/H.264+ Compression
- Day/Night
- True WDR 120dB
- Audio Input/Output
- Indoor Only
- 12VDC/PoE Operation
- Smart Analytics
- Free iOS & Android Apps for Smart Phones & Tablets
- Free Central Management Software (CMS) to manage multiple units & sites from a single platform
- Free MAC client software available to manage your system from your Apple computer

| | |
|-------------------------|--|
| Camera | ELEV-P4SMOKE |
| Sensor+DSP | OV4689+Hi3516D |
| Image Sensor | 1/3" Progressive scan CMOS Sensor |
| Min. Illumination | 0.01lux(Color) |
| Lens Mount | M12 |
| Lens | 2.8mm Lens |
| Shutter Time | Auto/Manual, 1/3~1/10000s |
| Day/Night | IR filter with auto switch |
| Wide Dynamic Range | WDR 120db |
| Digital noise reduction | 2D/3D DNR |
| Compression Standard | |
| Video Compression | H.264/H.264+/H.265/H.265+ |
| H.264 Codec profile | Base/Main/High profile |
| H.265 Codec profile | Main profile |
| Video Bit Rate | 11 Kbps~9 Mbps |
| Triple Streams | Support |
| Audio Compression | G.711A |
| Audio Bit Rate | 64 Kbps |
| Image | |
| Max. Image Resolution | 4MP(2560 × 1440) |
| Frame Rate | 50Hz: 25fps 4MP(2560 × 1440),23fps 4MP(2304 × 1728) 25fps 3MP(2048 × 1536),25fps 1080P(1920 × 1080) 25fps 960P(1280 × 960),25fps 720P(1280 × 720) 60Hz 28fps 4MP(2560 × 1440),26fps 4MP(2304 × 1728) 30fps 3MP(2048 × 1536),30fps 1080P(1920 × 1080) 30fps 960P(1280 × 960),30fps 720P(1280 × 720)" |
| Sub Stream | 50Hz:25fps D1(704 × 576),25fps CIF(352 × 288) 60Hz:30fps D1(704 × 480),30fps CIF(352 × 240)" |
| Third Stream | 50Hz:25fps CIF(352 × 288) 60Hz:30fps CIF(352 × 240)" |
| Image Setting | Brightness/Contrast/Saturation/Hue/Sharpness |
| BLC | Support |
| HLC | Support |
| ROI | Support |
| Defog | Support |
| Network | |
| Network Storage | NAS(NFS/CIFS) |
| Protocols | TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, NTP, IGMP, UPnP, SMTP, UPnP-TM, P2P, Bonjour |
| Event | Motion Detection, Tampering |
| Smart Functions | Area Intrusion, Line crossing, Object Missing, Unattended Object, Fast Moving |
| System compatibility | CGI |
| Security | User authentication,IP address filtering,Video mask |
| Mobile Surveillance | iPhone, iPad, Android devices |
| Interface | |
| Communication interface | 1 RJ45 10M / 100M Ethernet Port |
| Audio I/O | 1/1 |
| Reset button | Support |
| General | |
| Operating Conditions | -22°F ~ 140°F (-30°C ~ 60°C) Humidity 95% or less (non-condensing) |
| Power Supply | DC12V ± 10% |
| POE Supply | PoE (802.3af)(External) |
| Power Consumption | MAX. 6W |
| Dimensions | ø 4.72 × 2.28" (ø 120 × 58(H))mm |
| Weight | 0.88lbs (400g) |

Ordering Information

ELEV-P4SMOKE: 4 Megapixel Smoke Detector Housing, 2.8mm, White (Smoke Detector is Non-Functioning)