



ELEV-P5DRXIRN

5 Megapixel IP Plug & Play, Outdoor Dome, Fixed Lens, 98' IR Range, WDR, 12VDC

Features

- 5 Megapixel Resolution
- Fixed Lens
- True Day/Night with IR Range up to 98'
- Smart IRs
- H.264/H.265
- 15 FPS Recording and Live
- WDR
- Smart Analytics
- IP66 Weather Resistant
- IK10 Vandal Resistant
- 12VDC
- Free iOS & Android Apps for Smart Phones & Tablets
- Free Central Management Software (CMS)
- Free MAC Client

Model	ELEV-P5DRXIR28N
Sensor+DSP	IMX335+HI3516EV300
Sensor	1/2.8" Progressive scan CMOS Sensor
Min. Illumination	0.01lux(Color), 0lux(IR on)
Lens	2.8 mm@F1.8: horizontal FOV: 102°, vertical FOV:74°
Lens Mount	M12
IR	14milX18pcs SMD LED
IR Range	30m(98ft)
Smart IR	Support
Shutter Time	Auto/Manual, 1/3~1/10000s
Day/Night	IR cut filter with auto switch
Wide Dynamic Range	WDR
Digital noise reduction	2D/3D DNR
Compression Standard	
Video Compression	H.264/H.265
H.264 Codec profile	Base/Main/High profile
H.265 Codec profile	Main profile
Video Bit Rate	11 Kbps~10 Mbps
Dual Streams	Support
Image	
Max. Image Resolution	5MP(2592 x 1944)(default 15fps)
Frame Rate	50Hz:15fps 5MP(2592 x 1944) 15fps 4MP(2560 x 1440),15fps 4MP(2304 x 1728) 25fps 3MP(2048 x 1536),25fps 1080P(1920 x 1080) 25fps 960P(1280 x 960), 60Hz:15fps 5MP(2592 x 1944) 15fps 4MP(2560 x 1440),15fps 4MP(2304 x 1728) 30fps 3MP(2048 x 1536),30fps 1080P(1920 x 1080) 30fps 960P(1280 x 960),30fps 720P(1280 x 720)
Sub Stream	50Hz:25fps 720P(1280 x 720) 25fps D1(704 x 576),25fps CIF(352 x 288) 60Hz:30fps 720P(1280 x 720) 30fps D1(704 x 480),30fps CIF(352 x 240)
Image Setting	Brightness/Contrast/Saturation/Hue/Sharpness
BLC	Support
HLC	Support
ROI	Support
Defog	Support
Network	
Protocols	*TCP/IP,ICMP,HTTP,HTTPS,DHCP,DNS,DDNS,RTP,RTSP, RTCP,NTP,IGMP,UPnP,SMTP,UPnP-TM,P2P,Bonjour,IPv6, FTP*
Event	Motion Detection, Video Shelter
Smart Functions	Line Crossing,Area Intrusion,Region Entrance,Region Exiting,Fast Moving-Face Detection
System compatibility	CGI
Security	User authentication,IP address filtering,Video mask
Mobile Surveillance	iPhone, iPad, Android , CMS, WEB
Interface	
Communication interface	1 RJ45 10M / 100M Ethernet Port
General	
Operating Conditions	-22°F ~ 140°F (-30°C ~ 60°C) Humidity 95% or less (non-condensing) *
Power Supply	DC12V ± 10%
POE Supply	PoE (802.3af)
Power Consumption	MAX. 8.5W
Weather Proof	IP66
Vandalproof	IK10
Dimensions (W x D x H)	φ5.56" x 4.33"
Weight	1.19lb (540g)

Ordering Information

ELEV-P5DRXIR28N: 5 Megapixel Dome, 2.8mm