



IMHD4K-65

65" Ultra High Definition 4K Monitor 3840 x 2160
Image, HDMI, DVI, VGA, DisplayPort, Built-In Speaker

Features

- 4K UHD 3840 x 2160 resolution
- Anti-Burn-in™ technology prevents image ghosting
- Image Enhancer: 3D Comb Filter / Noise Reduction / Freeze
- Versatile connectivity: DisplayPort, HDMI, DVI, VGA
- Media Playback: play photos, videos and music from a USB drive or micro SD card
- An integrated scheduler allows content programming based on time and day
- Alink™ function for synchronized powering on/off via HDMI
- OPS slot for easy digital signage player integration
- RS232/LAN/IR control - provides compatibility with control systems
- Black-level adjustment for presenting more details in dark images
- Selectable gamma curves optimise different kinds of images
- Built-in speakers
- VESA mount compatibility for flexible installation

Model	IMHD4K-65
Panel Type	LED-Backlit TFT LCD (VA Technology)
Panel Size	64.5"
Max. Resolution	UHD 3840 x 2160
Pixel Pitch	0.372 mm
Brightness	350 cd/m ²
Contrast Ratio	4000:1
Viewing Angle (H/V)	178°/178°
Display Colour	1.07B
Response Time	5 ms
Surface Treatment	Anti-Glare Treatment (Haze 2%), 3H Hard Coating
Frequency	
Frequency (H)	31 kHz-92 kHz
Frequency (V)	48 Hz-85 Hz

Signal Input	
DisplayPort	x 1
HDMI	2.0 x 4
VGA	15-Pin D-Sub x 1
External Control	
IR In	3.5 mm Phone Jack
IR Out	3.5 mm Phone Jack
RS232 In	2.5 mm Phone Jack
RS232 Out	2.5 mm Phone Jack
LAN	RJ45 x 1
RJ11	Yes
Other Connectivity	
USB	2.0 x 1 (Service Port / Media Playback) / 2.0 x 1 (Media Playback) / 3.0 x 1 (Media Playback) / USB Power Outlet x 1 (5V2A)
OPS Slot	Yes
Micro SD Card Slot	Yes
Audio	
Audio In	Stereo Audio Jack (3.5 mm)
Audio Out	Stereo Audio Jack (RCA)
Internal Speakers	10W x 2
Power	
Power Supply	Internal
Power Requirements	AC 100-240V, 50/60 Hz
On Mode	186W (On)
Stand-by Mode	< 0.5W
Off Mode	< 0.5W
Operating Conditions	
Temperature	32°F-104°F (0°C-40°C)
Humidity	20%-80% (non-condensing)
Storage Conditions	
Temperature	-4°F-140°F (-20°C-60°C)
Humidity	10%-90% (non-condensing)
Mounting	
VESA FPMPMI	Yes (400 x 400 mm)
Security	
Kensington Security Slot	Yes
Dimensions	
Product w/o Base (W x H x D)	54.7" x 32.9" x 3.2" (1458.7 x 834.7 x 81.6 mm)
Packaging (W x H x D)	65.2" x 42.4" x 8.2" (1655.0 x 1078.0 x 280.0 mm)
Weight	
Product w/o Base	54.7 lb (24.8 kg)
Packaging	77.6 lb (35.2 kg)

Ordering Information

IMHD4K-65: 65" HD Monitor

InVid Tech, reserves the right to make changes to improve our products at any time without notice; we are not responsible for misprints.