



ELEV-8CHTX2MPKITAN

4-Camera, 2 Megapixel HD Analog Kit

- (4) 2-Megapixel Turret Cameras
- (1) 8-Ch DVR
- (4) 60' Coax Cables
- (1) Power Supply
- (1) HDMI Cable
- (1) Network Cable
- (1) Video Surveillance Warning Sticker



Easily Add to Your kit with InVid Tech HD Analog Cameras!



Kit Camera

2 Megapixel TVI/AHD/CVI/ CVBS, Outdoor Turret, 65' IR Range, D-WDR, 12VDC

Kit Camera Features

- 2 Megapixel 1080p (TVI/AHD/CVI) Resolution
- All-in-One Technology (TVI/AHD/CVI/Analog 960h)
- Fixed Lens
- D-WDR
- 65' IR Range
- Up The Cable (UTC) Function
- IP66 Weather Resistant
- 12VDC Only Operation
- Through InVid Tech DVR: Free App, CMS & MAC Client

Camera	2 MP Kit Camera
Image Sensor	1/2.9" CMOS Sensor
Signal System	PAL/NTSC
Effective Pixels	1920(H) x 1080(V)
Electronic Shutter	Auto
Min. Illumination	0.01Lux
Video Frame Rate	PAL/NTSC: 25/30 FPS
Video Output	AHD / TVI / CVI / CVBS
Default Video Output	TVI
Camera Features	
S/N Ratio	>41dB
Noise Reduction	2D DNR
Day&Night	Auto / Color / B&W
White Balance	Auto / Manual
OSD Language	English
AGC	Auto
Mirror Image	Yes
Auto Iris:	Yes
Sharpness	Yes
BLC	Yes
D-WDR	Yes
IR LED	18pcs SMD LED
IR Range	65' (20m)
Lens	
Focal Length	2.8mm fixed lens
Angle of View	H: 100°
Lens Type	Fixed Iris
Mount Type	M12
General	
IP Rating	IP66
Housing Material	Metal Ball with Plastic Base
Power Supply	DC12V(+/-10%)
Power Consumption	5W
Working Temperature / Humidity	-4°F-122°F (-20 ~ 50°C) RH95% MAX
Dimensions (Ø×H)	3.62" x 3.46" (92 x 88mm)
Weight	0.72 lb (330g)



ELEV-8CHTX2MPKITAN

4-Camera HD Analog Kit, 2-Megapixel

(4) 2-Megapixel Turret Cameras, (1) 8-Ch DVR, (4) 60' Coax Cables, (1) Power Supply, (1) HDMI Cable, (1) Network Cable (1) Video Surveillance Warning Sticker



Recorder

8 Ch TVI/AHD/CVI/Analog/IP Universal Port Recorder (5 MP), with 2 Bonus IP Ch (2/4 MP), Up to 10 cameras total, 1 HD Bay

Features

- 8 Channel Universal Port DVR (TVI/AHD/CVI/Analog/IP)
- Up to 5MP Support on HD Analog Channels
- 2 Bonus IP Channels
 - Up to 2 Megapixel in Hybrid IP Mode*
 - Up to 4 Megapixel in Full IP Mode**
- Total Max IP Input: 10 (Including Bonus IPC)
- H.265/H.265+/H.264/H.264+ Video Compression
- True P2P Connectivity with QR Code Connect
- Simultaneous HDMI/VGA up to 1080p Resolution
- CVBS Main or Spot Monitor
- HDMI up to 4K Resolution
- Supports up to 8 Channel Simultaneous Playback
- Multiple video search options including Smart and Thumbnail Search for quick retrieval of footage.
- Cloud Storage
- Cloud Upgradable
- Free iOS & Android Apps for Smart Phones & Tablets
- Free Central Management Software (CMS) to manage multiple units & sites from a single platform
- Free MAC client software to easily manage your system from your Apple computer

*Hybrid Mode:
Analog camera and IP camera can be added at the same time.

**Full IP Mode:
Convert all channel type to IP, only IP camera can be added

Ordering Info:

Kit Part Number: ELEV-8CHTX2MPKITAN

Model	Kit Recorder
Chipset	Hi3521D
Video & Audio Input	
Video Input	8ch BNC interface(1.0Vp-p, 75 Ω)
TVI	5MP,4MP,1080P, 720P
CVI	5MP,4MP,1080P, 720P
AHD	5MP,4MP,1080P, 720P
IPC	2CH 2MP in default mode; Up to 4MP in full IP mode
CVBS	Support
Audio Input	4ch, RCA(2.0 Vp-p, 1 KΩ)
Two way talk	1-ch, multiplex with Audio Input(RCA)
Video & Audio Output	
HDMI	1ch, resolution: 4K(3840×2160)/30Hz,1920×1080/60Hz,1280×1024/60Hz,1280×720/60Hz,1024×768/60Hz
VGA	1ch, resolution: 1920×1080/60Hz 1280×1024/60Hz, 1280×720/60Hz, 1024×768/60Hz
CVBS output	Support
Audio Output	1-ch, RCA (Linear, 1kΩ)
Recording	
Compression	H.265+/H.265/H.264+/H.264
Resolution	8ch 5MP Lite@12fps; 8ch 4MP Lite@15fps; 8ch 1080P@15fps;
Frame Rate(fps)	1-15fps
Video Bit Rate	11Kbps-8192Kbps
Audio Compression	G.711a
Audio Bit Rate	64kbps
Bonus IPC Input	
Resolution	1080P/960P/720P
Frame Rate	2MP/960P/720P @ 30FPS
IPC Input/Access Bandwidth	IPC x 2 / 20Mbps
IP Input	
Resolution	4MP/2MP/960P/720P
Frame Rate	4MP/2MP/960P/720P @ 30FPS
Toatal Access Bandwidth	60Mbps
Toatal Max IP Input	6 (including Bonus IPC)
Playback & Backup	
Playback Mode	Smart Playback/Normal/Time Division/ Label/ Event/ Picture Playback
Playback Rate	8ch Playback
Backup Mode	USB Device/Network/External HDD
Advanced Features	
Smart Detection for Analog	4CH line crossing detection,intrusion detection
Video Quality Detection	4CH Defocus Detection
Smart Detection for IPC	Line crossing detection,Area Intrusion detection
Smart Playback for Analog	Line Crossing/Are Intrution/Motion Detection
Smart Playback for IPC	Line Crossing/Are Intrution/Motion Detection
Cloud Storage	Support
Cloud Upgrade	Support
Network	
Ethernet	1 RJ-45 10 /100 Mbps self-adaptive Ethernet interface
Network Function	HTTPs, HTTP/TCP/IP,IPv4,UPnP, RTSP,RTCP, UDP, SMTP,SNMP,Multicast,IGMP,NTP, DHCP,DNS,DDNS, FTP, P2P
Smart Phone	IOS(iPhone, iPad), Android(Phone, Pad)
Hard Disk	
SATA	1 HDD
Capacity	Up to 10TB capacity for each HDD
External Interface	
Serial Interface	RS-485
USB Interface	Front panel: 1 × USB 2.0 Rear panel: 1 × USB 2.0
General	
Power Supply	DC12V,2A
Power Consumption	≤15W(without HDD)
Working Environment	-10°C~+55°C / 10%~90%RH
Dimension (W×D×H)	250 x 230 x 45mm