



ELEV-8CHTX5MPKITAN 4-Camera, 5 Megapixel HD Analog Kit

- (4) 5-Megapixel Turret Cameras
- (1) 8-Ch DVR
- (4) 60' Coax Cables
- (1) Power Supply
- (1) HDMI Cable
- (1) Network Cable
- (1) Video Surveillance Warning Sticker



Easily Add to Your kit with InVid Tech HD Analog Cameras!



Kit Camera

5-2 Megapixel Field Selectable TVI/
AHD/CVI/CVBS, Outdoor Turret, 65'
IR Range, D-WDR, up to -40, 12VDC

Kit Camera Features

- 5-2 Megapixel Field Selectable**
- All-in-One Technology (TVI/AHD/CVI/Analog 960h)
- Fixed Lens
- True Day/Night
- D-WDR
- 65' Smart IR Range
- Up The Cable (UTC) Function
- IP66 Weather Resistant
- Withstand up to -40° Operation
- 12VDC Only Operation
- Through InVid Tech DVR:
Free App, CMS & MAC Client

Model	5 MP Kit Camera
Image Sensor	1/2.5" CMOS Sensor
Signal System	NTSC/PAL
Effective Pixels	2592(H) x 1944(V)
Field of View	Horizontal: 102° Vertical:74°
Electronic Shutter	AUTO/ 1/50 1/60 -1/50,000sec
Min. Illumination	0.01Lux
Video Output	TVI:5MP 20/12.5 FPS, 4MP 30/25/12.5 FPS, 2MP 30/25 FPS AHD:5MP 20/12.5 FPS, 4 MP 30/25 FPS, 2MP 30/25 FPS CVI:4MP 30/25 FPS, 2 MP 30/25 FPS CVBS
Video Output By Default	TVI: 5MP @ 20 FPS AHD:2MP @ 30 FPS CVI: 2MP @ 30 FPS CVBS
Dip Switch	Support
UTC Control	Support
Camera Features	
Mirror Image	Yes
Auto Iris	No
Sharpness	Yes
Defogging	No
BLC	Yes
D-WDR	Yes
S/N Ratio	>41dB
Noise Reduction	2DNR
Day&Night	Color / B&W/ AUTO / EXT
White Balance	Manual/Auto
AGC	Auto
IR LED	18pcs SMD IR
IR Range	Up to 65 ft
Lens	
Focal Length	2.8mm Fixed Lens
Lens Type	Fixed Iris
Mount Type	M12
General	
IP Rating	IP66
Casing	Metal
Power Supply	DC12V(+/-10%)
Power Consumption	IR OFF:85mA / IR ON:320mA
Working Temperature / Humidity	-40°F-140°F(-40~+60°C)
Dimensions(W×D×H)	4.00" x 3.52"
Weight	.82 lbs (370g)

**Scale down to other resolutions via camera dip switches & OSD
InVid Tech, reserves the right to make changes to improve our products at any time without notice; we are not responsible for misprints.



ELEV-8CHTX5MPKITAN

4-Camera HD Analog Kit, 5-Megapixel

(4) 5-Megapixel Turret Cameras, (1) 8-Ch DVR, (4) 60' Coax Cables, (1) Power Supply, (1) HDMI Cable, (1) Network Cable, (1) Network Cable (1) Video Surveillance Warning Sticker



Recorder

8 Ch TVI/AHD/CVI/Analog/IP Universal Port Recorder (5 MP), with 2 Bonus IP Ch (2/4 MP), Up to 10 cameras total, 1 HD Bay

Features

- 8 Channel Universal Port DVR (TVI/AHD/CVI/Analog/IP)
- Up to 5MP Support on HD Analog Channels
- 2 Bonus IP Channels
 - Up to 2 Megapixel in Hybrid IP Mode*
 - Up to 4 Megapixel in Full IP Mode**
- Total Max IP Input: 10 (Including Bonus IPC)
- H.265/H.265+/H.264/H.264+ Video Compression
- True P2P Connectivity with QR Code Connect
- Simultaneous HDMI/VGA up to 1080p Resolution
- CVBS Main or Spot Monitor
- HDMI up to 4K Resolution
- Supports up to 8 Channel Simultaneous Playback
- Multiple video search options including Smart and Thumbnail Search for quick retrieval of footage.
- Cloud Storage
- Cloud Upgradable
- Free iOS & Android Apps for Smart Phones & Tablets
- Free Central Management Software (CMS) to manage multiple units & sites from a single platform
- Free MAC client software to easily manage your system from your Apple computer

*Hybrid Mode:
Analog camera and IP camera can be added at the same time.

**Full IP Mode:
Convert all channel type to IP, only IP camera can be added

Ordering Info:

Kit Part Number: ELEV-8CHTX5MPKITAN

Model	Kit Recorder
Chipset	HI3521D
Video & Audio Input	
Video Input	8ch BNC interface(1.0Vp-p, 75 Ω)
TVI	5MP,4MP,1080P, 720P
CVI	5MP,4MP,1080P, 720P
AHD	5MP,4MP,1080P, 720P
IPC	2CH 2MP in default mode; Up to 4MP in full IP mode
CVBS	Support
Audio Input	4ch, RCA(2.0 Vp-p, 1 KΩ)
Two way talk	1-ch, multiplex with Audio Input(RCA)
Video & Audio Output	
HDMI	1ch, resolution: 4K(3840×2160)/30Hz,1920×1080/60Hz,1280×1024/60Hz,1280×720/60Hz,1024×768/60Hz
VGA	1ch, resolution: 1920×1080/60Hz 1280×1024/60Hz 1280×720/60Hz 1024×768/60Hz
CVBS output	Support
Audio Output	1-ch, RCA (Linear, 1kΩ)
Recording	
Compression	H.265+/H.265/H.264+/H.264
Resolution	8ch 5MP Lite@12fps 8ch 4MP Lite@15fps; 8ch 1080P@15fps;
Frame Rate(fps)	1-15fps
Video Bit Rate	11Kbps-8192Kbps
Audio Compression	G.711a
Audio Bit Rate	64kbps
Bonus IPC Input	
Resolution	1080P/960P/720P
Frame Rate	2MP/960P/720P @ 30FPS
IPC Input/Access Bandwidth	IPC x 2 / 20Mbps
IP Input	
Resolution	4MP/2MP/960P/720P
Frame Rate	4MP/2MP/960P/720P @ 30FPS
Total Access Bandwidth	60Mbps
Total Max IP Input	6 (including Bonus IPC)
Playback & Backup	
Playback Mode	Smart Playback/Normal/Time Division/ Label/ Event/ Picture Playback
Playback Rate	8ch Playback
Backup Mode	USB Device/Network/External HDD
Advanced Features	
Smart Detection for Analog	4CH line crossing detection,intrusion detection
Video Quality Detection	4CH Defocus Detection
Smart Detection for IPC	Line crossing detection,Area Intrusion detection
Smart Playback for Analog	Line Crossing/Are Intrution/Motion Detection
Smart Playback for IPC	Line Crossing/Are Intrution/Motion Detection
Cloud Storage	Support
Cloud Upgrade	Support
Network	
Ethernet	1 RJ-45 10 /100 Mbps self-adaptive Ethernet interface
Network Function	HTTPs, HTTP,TCP/IP,IPv4,UPnP,RTSP,RTCP, UDP, SMTP,SNMP,Multicast,IGMP,NTP, DHCP,DNS,DDNS, FTP, P2P
Smart Phone	IOS(iPhone, iPad), Android(Phone, Pad)
Hard Disk	
SATA	1 HDD
Capacity	Up to 10TB capacity for each HDD
External Interface	
Serial Interface	RS-485
USB Interface	Front panel: 1 × USB 2.0 Rear panel: 1 × USB 2.0
General	
Power Supply	DC12V,2A
Power Consumption	≤15W(without HDD)
Working Environment	-10°C~+55°C / 10%~90%RH
Dimension (W×D×H)	250 x 230 x 45mm
Weight	1.5kg