



INVID-SP30W

30W IP Horn Speaker with MIC

Features

- Two-way intercom communication
- PoE eliminates need for local power supply
- 48K OPUS Audio Codec enables excellent sound quality
- Compatible with VoIP, SIP devices (IPPBX, IP Phone) via SIP
- Compatible with IP Camera VMS via ONVIF
- Support Pre-recorded messages
- Support HPPT API for alarm in transmit

Specs	INVID-SP30W
Audio	
Codec	OPUS 48 kHz, MP3 44.1 kHz, G.722 ADPCM 16 kHz, G.711 PCMU 8 kHz, G.711 PCMA 8 kHz
Built-in Microphone	Yes
Speaker	
Max SPL	120dB
Frequency Response	350Hz~8KHz
Frequency Range	500-2KHZ +10dB 400-12KHZ +20dB
Harmonic Distortion	0.1@1kHz
Signal to Noise Ratio	91dB
Network	
Security:	Password protection, IP address filtering, Digest authentication, User access log, firewall
Network Protocol	SIP, ONVIF, HTTP, IPv4, DHCP, RTSP, RTP, RTCP, TCP, UDP, ARP, FTP, TFTP, NFS, NTP
Network Interface	10/100 Base-TX, RJ45
VoIP	Support for SIP protocol for intergration with VoIP systems, intergrated with SIP/PBX. 2 SIP Accounts, SIP Direct IP Call, RTP Multicast Codec: OPUS, MP3, G.722, PCMU, PCMA
Amplifier	
Amplifier Description	Built-in 30W Amplifier
General	
Operating Temperature	-22°F ~ 140°F(-30°C ~ 60°C)
Operating humidity	5%-85%
Material	ABS (IP67 water-proof)
Rate Power	30W
Power Supply	PoE or DC 12V/24V
Connector	Alarm in, Audio in, DC Power, PoE, TF Card (Optional)
Installation	Wall Mounted
Dimensions	11.2 x 8.1 x 11.4 in (285*205*290mm)
Net Weight	4.4 lbs (2 KG)
Languages	English
Warranty	2 years

Ordering Information

INVID-SP30W: IP Horn speaker