



INVID-AIR-B No Touch Exit Button is widely used in access control and security applications where ondemand passage opening control is required.

The unit's small size and stylish design extend installation options to narrow door trims or wall panels.

And its easy-to-see light indicator makes it easy to locate the button when the device is installed in poorly lit areas.

INVID-AIR-B provides efficient and convenient access control, minimizes false alarms, and ensures safe passage through doorways, making it an essential component in security and access control systems.

* Additional wires are required to connect the door.

INVID-AIR-B

Button No Touch Configurable

Features

- High Durable Output
- Selectable Delay 0.5-10s
- Sound Control

- Two Work Modes
- Selectable Distance 0-50cm
- Wide Voltage Range

Device Specifications	
Sensor type	Laser
Distance	3.93"/7.88"/11.81"/19.68" (10/20/30/50 cm)
Indication	2 color LED
Buzzer	Yes
Open delay, second	0.1/3/6/9
Physical connections	
Green wire (input)	Green indication status
Blue wire (Aux Out)	Open collector
Electrical characteristics	
Input voltage	12-24 VDC +/- 10 %
Operation current (MAX) 12 VDC	0.11 A (1.3 W)
Switching current (MAX) 12 VDC Aux Out	0.2 A (4 W)
Output short-circuit protection	Yes
Power supply reverse polarity protection	Yes
Environmental requirements	
Operating temperature	-22°F ~ 158°F (-30°C ~ 70°C)
Ingress Protection rating	IP65
Physical characteristics	
Housing material	ABS plastic UL94 V-0
Mounting method	Wall mount
Dimensions (diameter, height)	2.36" x 0.67" (60 x 17 mm) (mounting ring) 2.36" x 0.86" (60 x 22 mm)
Weight	1.59 oz (45 g)





Ordering Information

INVID-AIR-B: Access Control Device

 $InVid\ Tech,$ reserves the right to make changes to improve our products at any time without notice; we are not responsible for misprints.