



\*Image above is IMHD-22FLUSH2 with mounting ears

## IMHD-22FLUSH2

22" 1920×1080 Flush Case Monitor, Built for 24/7 Performance

### Features

- Built for 24/7 performance, ensuring continuous, reliable video surveillance for critical security environments
- Portrait Mode Support
- Physical resolution of 1920×1080
- 5ms fast response time, no image ghosting
- Adapt newest 3D digital filtering and 3D digital noise reduction technology
- Picture fast response; 178° wide viewing angle; Ensure that the image display is not deformed
- High fidelity digital processing, brilliant and vivid video
- Humanize Menu; Convenient Controller
- VESA 75x75, 100x100



### Ordering Information

**IMHD-22FLUSH2:** 22" Flush Case Monitor

| Display Characteristics     |   |
|-----------------------------|---|
| Model Name                  | IMHD-22FLUSH2   |
| Screen Size                 | 22"   |
| Active Display Area (W x H) | 476.64mm(W)×268.11mm(H)                               |
| Display Mode                | 16:9  |
| LED Type                    | TFT-LED   |
| Resolution                  | 1920 × 1080   |
| Display Color               | 16.7M   |
| Pixel Pitch(mm)             | 0.294(H)×0.294(V)                                     |
| Brightness(nits)            | 300cd/m 2   |
| Contrast Ratio              | 1000:1  |
| Viewing Angle               | 178(H) /178(V)  |
| Response Time               | 5ms   |
| Backlight                   | LED   |
| Input & Output              |   |
| HDMI                        | 1   |
| VGA                         | 1   |
| BNC input                   | 2   |
| BNC output                  | 1   |
| Video                       |   |
| Color System                | PAL/NTSC/SECAM  |
| Compatible HDTV input       | 480P,576P,720P,1080I, 1080P                           |
| 3D comb filter              | Yes   |
| Video Noise Reduction       | Yes   |
| Power & Mount Way           |   |
| Power                       | DC12V ,50/60Hz  |
| Working Temperature         | -22°F ~ 185°F (-30°C ~ 85°C)                          |
| Power Consumption           | <13W  |
| Menu                        | English(other languages supported)                    |
| Mounting/Weight             | Stand mount, VESA mount/ 11lb (5kg)                   |
| MTBF                        | 50000Hours  |
| Accessories                 |   |
| Included Accessories        | Industrial PSU,Screw, Cable holder, Quick start guide |

