



IMHD-24PVM-C

24" 1080P IP Circular PVM Monitor, Built for 24/7 Performance

Features

- Built for 24/7 performance, ensuring continuous, reliable video surveillance for critical security environments
- Built in 1080p IP camera
- 120dB WDR for IPC
- 1920 x 1080 Resolution
- 350cd/m² Brightness
- 5ms fast response time, no Image Ghosting
- HDMI 2.0 Input
- VGA Input

Model Name	IMHD-24PVM-C
Screen Size	24"
Active Display Area (mm)	521.28mm(W)×293.22mm(H)
Display Mode	16:9
LED Type	TFT-LED
Resolution	1920 × 1080
Display Color	16.7M
Pixel Pitch(mm)	0.1926(H)×0.1790(V)
Brightness(nits)	350cd/m ²
Contrast Ratio	1000:1
Viewing Angle	178(H) /178(V)
Response Time	5ms
Backlight	LED
Input & Output	
HDMI/VGA	2/1
Remote control	1
USB input (image input)	1
Network(POE)/LAN OUT STORAGE	1
SD Card record	0
IP Camera	

H.265 2.0mp IP Camera Module, support NDAA

1920 (H) X 1080 (V) approx. 2 million pixels

Main stream: 1920X1080, 1280X720 (1~25/30fps)

Support ONVIF/GB28181/SDK

Power & Mount Way	
Power	AC100-240V ,50/60Hz
Working Temperature	-22°F ~ 185°F(-30°C ~ 85°C)
Power Consumption	<30W
Menu	English(other languages supported)
Mounting/Weight	Stand mount, VESA mount/ 26.5lbs (12kg)
MTBF	50000Hours
Accessories	
Included Accessories	Industrial PSU,Screw, Cable holder, Quick start guide

Ordering Information

IMHD-24PVM-C: 24" Circular PVM Monitor

InVid Tech, reserves the right to make changes to improve our products at any time without notice; we are not responsible for misprints.