



IMHD-32PVM2HDMI

32" 1080P IP PVM Metal Case Monitor

Features

- Industrial level DID LCD panel, suitable for extensive 24 x 7 continuous works
- Physical resolution of 1920x1080
- 5ms fast response time, no image ghosting
- Adapt newest 3D digital filtering and 3D digital noise reduction technology
- Built in 1080p IP camera
- High fidelity digital processing, brilliant and vivid video
- 120dB true WDR to provide balanced images, ensuring highly detailed images are seen
- Humanize Menu; Convenient Controller

Model Name	
Screen Size	32"
Active Display Area (W x H)	27.5 x 15.4 in (697.6845 x 392.256mm)
Display Mode	16:9
LED Type	TFT-LED
Resolution	1920 x 1080
Display Color	16.7M
Pixel Pitch (H x V)	0.51075 x 0.51075mm
Brightness(nits)	350cd/m ²
Contrast Ratio	1300:1
Viewing Angle	178(H) /178(V)
Response Time	5ms
Backlight	LED
Input & Output	
HDMI/VGA	2/1
BNC input (signal input)	1
BNC output (signal output)	1
Network/LAN OUT STORAGE	1
SD Card record	1
IP Camera	
H.265 2.0mp IP Camera Module, support NDA	
1920 (H) X 1080 (V) approx. 2 million pixels	
Main stream: 1920X1080, 1280X720 (1~25/30fps)	
Support ONVIF/GB28181/SDK	
Power & Mount Way	
Power	AC100V~240V/ 90W input
Working Temperature	-22°F ~ 185°F (-30°C ~ 85°C)
Consumption	<40W
Menu	English
Mounting	Stand mount, VESA mount
Weight	44.1 lbs (20kg)
MTBF	50000Hours
Accessories	
Included Accessories	Industrial PSU, Screw, Cable holder, Quick start guide

Ordering Information

IMHD-32PVM2HDMI: 32" PVM Monitor