




IMHD4K-43DSB

43" all-in-one 4K UHD Digital Signage Display

Features

- Ultra HD 3840 x 2160 resolution
- 500 nits brightness panel offers clear images even in well-lit environments
- 8.7mm ultra-narrow bezel for a seamless and immersive viewing experience
- · Slim profile of 40mm fits closely to the wall, ensuring a sleek, integrated look
- 25% haze anti-glare for a glare-free viewing experience in any lighting condition
- Anti-Burn-in[™] technology prevents image ghosting
- · Premium commercial-grade panel designed for 24/7 use
- Flexible display orientation, with landscape and portrait options
- Android 9.0 & 16GB Storage capacity for apps and media
- USB media playback directly from USB storage devices quickly and easily
- Built-in Wi-Fi 5 and Bluetooth options for easy integration into your existing network and connection to peripheral devices
- Integrated web browser on accessing online content directly from your display
- Wireless screen sharing without any apps downloaded
- User-friendly content management system offers an intuitive interface for updating and scheduling content with ease
- Embedded advanced content scheduling function for easy arrangement of content playback schedule
- $3 \times \text{HDMI}$ ports provide connections to an external media player and a variety of HD sources
- RS232 & LAN control for incorporation into a managed network for centralized control



Ordering Information

IMHD4K-43DSB: 43" 4K Digital Signage Display

 ${\it InVid Tech, reserves the right to make changes to improve our products at any time without notice; we are not responsible for misprints.}$

Panel	
Panel Type	VA
Panel Size	42.5"
Max. Resolution	UHD 3840 x 2160
Pixel Pitch	0.245 mm
Brightness	500 cd/m ²
Contrast Ratio	4000:1
Viewing Angle (H/V)	178°/178°
Display Color	1.07G
Response Time	5 ms
Surface Treatment	Haze 25%, Hard Coating (3H)
Frequency	
Frequency (H)	18 kHz-135 kHz
Frequency (V)	24 Hz-60 Hz
Signal Input	
HDMI	2.0 × 3
External Control	
RS232 In	9-Pin D-Sub
LAN	RJ45 x 1
Embedded Player	
OS	Android 9.0
CPU	A35*4
Memory	2G
Storage	16G
Other Connectivity	
USB	2.0 x 2 (Service Port / Media Playback)
Audio Out	Stereo Audio Jack (3.5 mm)
Internal Speakers	10W x 2
Power	
Power Supply	Internal
Power Requirements	AC 100-240V, 50/60 Hz
On Mode	73W (On)
Standby Mode	< 0.5W
Operating Conditions	
Temperature	32°F-104°F (0°C-40°C)
Temperature Humidity	32°F-104°F (0°C-40°C) 20%-80% (non-condensing)
Humidity	
Humidity Storage Conditions	20%-80% (non-condensing)
Humidity Storage Conditions Temperature	20%-80% (non-condensing) -4"F-140"F (-20"C-60"C)
Humidity Storage Conditions Temperature Humidity	20%-80% (non-condensing) -4"F-140"F (-20"C-60"C)
Humidity Storage Conditions Temperature Humidity Mounting	20%-80% (non-condensing) -4"F-140"F (-20"C-60"C) 20%-80% (non-condensing)
Humidity Storage Conditions Temperature Humidity Mounting VESA FPMPMI	20%-80% (non-condensing) -4"F-140"F (-20"C-60"C) 20%-80% (non-condensing)
Humidity Storage Conditions Temperature Humidity Mounting VESA FPMPMI Dimensions	20%-80% (non-condensing) -4"F-140"F (-20"C-60"C) 20%-80% (non-condensing) 400 mm x 300 mm
Humidity Storage Conditions Temperature Humidity Mounting VESA FPMPMI Dimensions Product w/o Base (W x H x D)	20%-80% (non-condensing) -4"F-140"F (-20"C-60"C) 20%-80% (non-condensing) 400 mm x 300 mm 38.1 x 21.9 x 1.6 in (967.4 x 555.9 x 40.0 mm)
Humidity Storage Conditions Temperature Humidity Mounting VESA FPMPMI Dimensions Product w/o Base (W x H x D) Packaging (W x H x D)	20%-80% (non-condensing) -4"F-140"F (-20"C-60"C) 20%-80% (non-condensing) 400 mm x 300 mm 38.1 x 21.9 x 1.6 in (967.4 x 555.9 x 40.0 mm) 42.3 x 25.7 x 5.7 in (1075.0 x 652.0 x 144.0 mm)
Humidity Storage Conditions Temperature Humidity Mounting VESA FPMPMI Dimensions Product w/o Base (W x H x D) Packaging (W x H x D) Weight	20%-80% (non-condensing) -4"F-140"F (-20"C-60"C) 20%-80% (non-condensing) 400 mm x 300 mm 38.1 x 21.9 x 1.6 in (967.4 x 555.9 x 40.0 mm) 42.3 x 25.7 x 5.7 in (1075.0 x 652.0 x 144.0 mm) 20.0 lb (91 kg)
Humidity Storage Conditions Temperature Humidity Mounting VESA FPMPMI Dimensions Product w/o Base (W x H x D) Packaging (W x H x D) Weight Packaging	20%-80% (non-condensing) -4"F-140"F (-20"C-60"C) 20%-80% (non-condensing) 400 mm x 300 mm 38.1 x 21.9 x 1.6 in (967.4 x 555.9 x 40.0 mm) 42.3 x 25.7 x 5.7 in (1075.0 x 652.0 x 144.0 mm) 20.0 lb (91 kg)
Humidity Storage Conditions Temperature Humidity Mounting VESA FPMPMI Dimensions Product w/o Base (W x H x D) Packaging (W x H x D) Weight Packaging Regulation Approval	20%-80% (non-condensing) -4"F-140"F (-20"C-60"C) 20%-80% (non-condensing) 400 mm x 300 mm 38.1 x 21.9 x 1.6 in (967.4 x 555.9 x 40.0 mm) 42.3 x 25.7 x 5.7 in (1075.0 x 652.0 x 144.0 mm) 20.0 lb (9.1 kg) 26.5 lb (12.0 kg)

