



PAR-P2BSSXIR36A

2 Megapixel IP Outdoor Stainless Steel Bullet, Fixed Lens,
65' EXIR Range, PoE/12VDC

Features

- 2 Megapixel (1920x1080) Resolution
- H.264/MPEG4/MJPEG Compression
- True Day/Night
- 30 FPS Recording and Live
- Fixed Lens
- EXIR Range up to 65'
- Stainless Steel Housing (Grade Steel | AISI 316)
- IP68 Waterproof
- 12VDC/PoE Operation
- ONVIF

Model	PAR-P2BSSXIR36A
Image Sensor	Sony Exmor CMOS image sensor
Size	1/2.9 inch
Scan System	Progressive Scan
Total Pixels	2000(H) x 1121(V), 2.24 Mega Pixels
Effective Pixels	1984(H) x 1105(V), 2.19 Mega Pixels
Day & Night	Auto / Day(Color) / Night(BW), ICR Control
Privacy Area	On / Off (6 Programmable Zones)
Motion Detection	48 Zone, Sensitivity 1 ~ 5 Step, On / Off
WDR	BLC / DWDR(1 ~ 5 Step) On / Off
3-DNR	Digital Noise Reduction, 1 ~ 63 Step
Elec. Shutter	Auto(1/15~1/15000), Suppress Rolling, Manual
Color adjust	Bright / Contrast / Saturation / Sharp / Hue
White Balance	Auto / Indoor / Outdoor / Fluorescent
OSD Display	Text, Data, Time, Event, On / Off
Image Mirror	Normal / Mirror(H) / flip(V) / Both(HV)
Ext. Video	VBS 1.0Vp-p
Housing	IP68 Waterproof, Grade Steel AISI 316
IR Range	65'
Power Supply	DC12[V] ± 10%
Operating Temperature	-4°F ~ 140°F (-20°C ~ 60°C)
Humidity	0% ~ 90%
Lens	3.6mm MP lens (ICR)
Dimensions Ø x L x H	2.3x 5 x 4.1 Inches (58 x 126 x 104)
Weight	2.2lbs (1002 grams) Approx

Ordering Information

PAR-P2BSSXIR36A: 2 Megapixel Stainless Steel Bullet, 3.6mm