



PAR-P2BSSXIRA2812

2 Megapixel IP Outdoor Stainless Steel Bullet,
Motorized A/F 2.8-12mm, 65' EXIR Range, PoE/12VDC

Features

- 2 Megapixel (1920x1080) Resolution
- H.264/MPEG4/MJPEG Compression
- True Day/Night
- 30 FPS Recording and Live
- Motorized Auto-Focus 2.8-12mm Lens
- EXIR Range up to 65'
- Stainless Steel Housing (Grade Steel I AISI 316)
- IP68 Waterproof
- 12VDC/PoE Operation
- ONVIF

Model	PAR-P2BSSXIRA2812
Image Sensor	Sony Exmor CMOS image sensor
Size	1/2.9 inch
Scan System	Progressive Scan
Total Pixels	2000(H) x 1121(V), 2.24 Mega Pixels
Effective Pixels	1984(H) x 1105(V), 2.19 Mega Pixels
Min. Illumination	0.005 Lux & 0 Lux with IR ON
Day & Night	Auto / Day(Color) / Night(BW), ICR Control
Privacy Area	On / Off (6 Programmable Zones)
Motion Detection	48 Zone, Sensitivity 1 ~ 5 Step, On / Off
WDR	BLC / DWDR(1 ~ 5 Step) On / Off
3-DNR	Digital Noise Reduction, 1 ~ 63 Step
Elec. Shutter	Auto(1/15~1/15000), Suppress Rolling, Manual
Color adjust	Bright / Contrast / Saturation / Sharp / Hue
White Balance	Auto / Indoor / Outdoor / Fluorescent
OSD Display	Text, Data, Time, Event, On / Off
Image Mirror	Normal / Mirror(H) / flip(V) / Both(HV)
Ext. Video	VBS 1.0Vp-p
Housing	IP68 Waterproof, Grade Steel I AISI 316
IR Range	65 Feet
Power Supply	DC12[V] ± 10%
Operating Temperature	-4°F ~ 140°F (-20°C ~ 60°C)
Humidity	0% ~ 90%
Lens	2.8~12mm DC auto iris motorized MP lens
Dimension (Ø x L x H)	2.83 x 6.63 x 4.72 inches (Ø72 x 168.5 x 120mm)
Weight	3.86 lbs (1520 grams)

Ordering Information

PAR-P2BSSXIRA2812: SS 2 Megapixel IP Bullet, 2.8-12mm Motorized