



## PAR-P2FACETXIR722G2

2 Megapixel IP Plug & Play Outdoor Turret, True Facial Recognition with NVR, 7-22mm Auto-Focus Motorized, White Light Detection, True WDR, Built-in Mic, SD Card Slot, PoE/12VDC

### Features

- 2 Megapixel (1920x1080) Resolution
- Motorized Auto-Focus 7-22mm Lens
- True Facial Recognition Capable with Compatible NVR
- White Light Detection for True Facial Recognition
- True Day/Night
- Starlight Illumination
- H.265+, H.265, H.264+, H.264, MJPEG Compression
- 30 FPS Recording and Live
- True WDR
- White Light Range up to 32'
- SD Card Local Storage, 256GB
- Audio Input: Built-In Mic
- IP67 Weatherproof
- 12VDC/PoE Operation
- ONVIF
- Smart Analytics
- Free iOS & Android Apps for Smart Phones & Tablets
- Free Central Management Software (CMS)
- Free MAC Client

Camera	PAR-P2FACETXIR722G2
Image Sensor	1 / 2.8" CMOS
Image Size	1920 x 1080
Electronic Shutter	1/ 25 s ~ 1 / 100000 s
Iris Type	DC-IRIS
Min. Illumination	0.0026 lux@F1.2, AGC ON; 0 lux with LED 0.005 lux@F1.6, AGC ON; 0 lux with LED
Lens	7~22mm@F1.6, motorized; Recommended face capturing distance: 4~10m
Field of View	Horizontal: 44~17.6°; Vertical:25.6~10°; Diagonal: 49.7~20.2°
Lens Mount	Ø14
Wide Dynamic Range	120dB
BLC	Yes
HLC	Yes
Defogging	Yes
Digital NR	3D DNR
Angle Adjustment	Pan: 0~360°; Tilt 0~80°; Rotation: 0~360°

### Ordering Information

**PAR-P2FACETXIR722G2:** 2 Megapixel, 7-22mm Lens, With True Facial Recognition

InVid Tech, reserves the right to make changes to improve our products at any time without notice; we are not responsible for misprints.

Image	
Video Compression	Main stream: Smart H.265 / H.265+ / H.265 / Smart H.264 / H.264+ / H.264 Sub stream: H.265+ / H.265 / H.264+ / H.264 / MJPEG Third stream: H.265+ / H.265 / H.264+ / H.264 / MJPEG
H.264 Compression Standard	Baseline Profile/ Main Profile / High Profile
Resolution	1080P (1920 x 1080), 720P (1280 x 720), D1, CIF, 480 x 240
Main Stream	60Hz : 1080P/ 720P (1~30fps); 50Hz : 1080P/ 720P (1~25fps ) HFR mode: 1080P/720P (60Hz: 1~60fps; 50Hz: 1~50fps)
Sub Stream	60Hz : 720P/D1/CIF (1~30fps); 50Hz:720P/D1/CIF (1~25fps)
Third Stream	60Hz : D1/CIF/480 x240 (1~30fps); 50Hz: D1/CIF/480 x240 (1~25fps)
Bit Rate	64 Kbps ~ 6 Mbps
Bit Rate Type	VBR/CBR
Image Settings	ROI, Saturation, Brightness, Chroma, Contrast,Wide Dynamic, Sharpen, NR, etc. adjustable through client software or web browser
Audio Compression	G711A/U
ROI	Each ROI to be configured separately
Interfaces	
Network	RJ45
Video Output	No
Audio	1CH audio input; 1CH built-in MIC
Storage	Built-in Micro SD Card Slot, up to 256 GB
Reset	Yes
Functions	
Remote Monitoring	Web Browsing, CMS Remote Control
Online Connection	Support simultaneous monitoring for up to 10 users; Support multi-stream real time transmission
Network Protocol	UDP, IPv4, IPv6, DHCP, NTP, RTSP, RTP, RTCP, ICMP, IGMP, FTP, PPPoE, DDNS, SMTP,SNMP,HTTP, 802.1x, UPnP, HTTPs, QoS
Interface Protocol	ONVIF
Storage	Network remote storage; micro SD card storage
Smart Alarm	Motion Detection; SD Card error, SD Card full
Intelligent Analytics	Face detection, face capture, face match, video blur detection, video color cast detection, scene change detection
General Function	Watermark, IP address filtering, video mask, heartbeat, password protection, non-photosensitive switch, face exposure
PoE	Yes (802.3af)
LED View Distance	32 ft (10m) soft light
Ingress Protection	IP67
Face Detection	
Face Detection	Pupil Distance of facial image over 20 pixel can be detected
Face Capturing	By precision detecting, tracing, capturing, scoring, and screening the faces to get the most effective face snapshots
Panorama Capturing	Support panorama capturing and self-defined information overlay, like device ID, Time, etc.
Intelligent Light Compensation	Built-in high efficient white light LEDs, time switch available
Face Picture Database	10000 face pictures
Database Management	Add, modify, delete and search face pictures
Face Picture Adding	Add face pictures through WEB and Face Album Manager Tool
External Face Picture Enrollment	Size: less than 70KB Format: jpg, jpeg
Face Picture Comparison Alarm	Support face trigger modes Support allow list, block list, stranger alarms
Others	
Power Supply	DC12V/PoE
Power Consumption	<1W
Operating Environment	-22°F ~ 140°F (-30°C ~ 60°C) humidity: Less than 95% (Non-condensing)
Dimensions	4.3 x 4.9 in (111.5 x 99.6mm)
Weight	Approx. 1.4 lbs (0.64KG)
Installation	Wall mounting; ceiling mounting
Certificate	CE, FCC
Environmental Protection	Complies with Directive EU RoHS, WEEE(2012/19/EU) , directive 94/62/EC and REACH(EC1907/2006)