



## PAR-P4CUBENH-AIT

4 megapixel Cube Wi-Fi Network Camera, Indoor only, 12VDC/PoE

### Features

- Supports Human/Vehicle Classification for Line Crossing Intrusion Detection
- Supports Person Detection within Field of View
- Supports PIR Detection up to 15'
- Max. resolution: 4MP (2560×1440)
- Deterrent Siren Linkage: Person, PIR, Line Crossing Intrusion Detection
- 32' IR night view distance
- Micro SD Slot: Up to 256GB
- Built-in Mic/Built-in Speaker
- Support 2.4G Wi-Fi
- Support mobile app for remote management and viewing of devices
- DC12V/PoE power supply
- Support P2P

Camera	
Image Sensor	1/3" Progressive Scan CMOS
Image Size	2560×1440
Electronic Shutter	1/3 s ~ 1/100000s
IRIS Type	Fixed IRIS
MIN. Illumination	Color: 0.0035lux@F1.2,AGC ON; B&W: 0 lux with IR
Lens	2.1mm @F2.1; horizontal field of view: 137°
Lens Mount	M12
WDR	78dB
BLC	Yes
HLC	Yes
Defog	No
DNR	2D/3D NR
Angle Adjustment	Pan: 0 ~230° ; Tilt: 0 ~71° ; Rotate: 0 ~360°
Image	
Video Compression	Main stream: H.265+/ H.265/H.264+/H.264 Sub stream: H.265+/ H.265/H.264+/H.264/MJPEG
H.264 Compression Standard	Baseline Profile/Main Profile/High Profile
Bit rate Type	VBR/CBR
Bit Rate	64Kbps ~ 6Mbps

### Ordering Information

**PAR-P4CUBENH-AIT:** 4 megapixel Cube Camera

InVid Tech, reserves the right to make changes to improve our products at any time without notice; we are not responsible for misprints.

Resolution	4MP (2560×1440), 3MP (2304×1296) , 1080P (1920×1080) , 720P(1280×720) , D1, CIF
Main Stream	4MP/3MP/1080P/720P (60Hz:1~30fps; 50Hz: 1~25fps)
Sub Stream	720P/D1/VGA/640×360/480×240/CIF (60Hz:1~30fps; 50Hz: 1~25fps)
Image Setting	Saturation, hue, brightness, contrast, wide dynamic range, sharpness, NR, image flip, etc., adjustable through client or web browser
Audio Compression	G711A/U
Region of Interest	8 regions of interest; each region can be configured separately
APP/Cloud	
WIFI Configuration	Configure Wi-Fi network by scanning the QR Code
Snapshot	Yes
Record	Yes
Two-way Audio	Yes
Listen	Yes
Storage	SD card storage
Playback	SD card storage
Sharing Device	Support sharing with up to 10 users
Interface	
Network Interface	100M RJ45
Audio	Built-in MIC×1, built-in speaker×1; echo cancellation supported
Alarm	1CH alarm input; 1CH alarm output
Reset Button	Yes
PIR	Horizontal angle: 100° ; Range: 5m
Storage	Built-in micro SD card slot, up to 256G
WiFi	2.4G WiFi function, IEEE802.11b/g/n Up to 50m wireless range
Indicator	Yes
Function	
Remote Monitoring	Web Client/NVR/Paramont CMS 2.0/ Paramont CMS Mobile APP
Online Connection	Support simultaneous monitoring for up to 3 users and multi-stream real time transmission
Network Protocol	UDP, IPv4, IPv6, DHCP, NTP, RTSP, PPPoE, DDNS, SMTP, SNMP, FTP, 802.1x, UPnP, HTTPS, HTTP, HTTP POST, RTMP, QoS, P2P
Interface Protocol	ONVIF Profile M
Storage	Network remote storage
Smart Alarm	Motion detection, sensor alarm, PIR alarm, audio alarm, Person detection alarm, SD card full, SD card error, IP conflict, cable disconnection, video exception
Intelligent Analytics	Line crossing detection/region intrusion detection (human/vehicle classification)
General Function	Watermark, IP address filtering, video mask, illegal login lock, disarming, cloud upgrade, ANR
IR Light Distance	32'
Water-proof Grade	No
PoE	Yes, IEEE802.3af
Others	
Power	DC12V/POE
Power Consumption	<5W
Environmental Protection	RoHS 2.0 REACH WEEE directive94/62/EC
Working Environment	-4°F ~ 122°F(-20°C ~ 50°C) , Humidity: less than 95% (non-condensing)
Dimensions	5.1 x 2.8 x 2.8 in (130 × 71.7 × 71.7mm)
Weight (net)	Approx. .3 lbs (0.14KG)
Installation	Wall mounting; Ceiling mounting desktop mounting

