



PAR-P4TXIRL28NH-AI

4 Megapixel IP Plug & Play, Outdoor Turret, 24/7 Full-Color Day AND Night, White Light up to 98', True AI, Fixed lens, Audio Input: Built-in Mic, Audio Output, SD Card Slot, 12VDC/PoE

Features

- True AI Human and Vehicle Classification for Line Crossing and Intrusion Detection
- 24/7 Full-Color Day & Night with InVid Tech Illuminate
- 4 Megapixel Resolution
- Fixed Lens
- White Light up to 98'
- H.265+ / H.265 / H.264+ / H.264
- 30 FPS Recording and Live
- SD Slot For Local Storage: Up to 1 TB
- Audio Input: Built-in Mic
- Audio Output
- IP67 Weatherproof
- 12VDC/PoE Operation
- ONVIF
- Free iOS & Android Apps for Smart Phones & Tablets
- Free Central Management Software (CMS)
- Free MAC Client
- NDA Compliant

Camera	PAR-P4TXIRL28NH-AI
Image Size	1 / 1.79 "CMOS
Image Sensor	2688 × 1520
Electronic Shutter	Auto or manual mode; manual mode: 1 / 2s ~ 1 / 100000 s
Iris Type	Fixed Iris
Min. Illumination	0.0003 lux @F1.0, AGC ON; 0 lux with illumination on
S/N Ratio	≥50dB
Lens	2.8 mm@F1.0, H.FoV: 112°; V.FoV:61°; D.FoV:133°
Focus	Fixed
Lens Mount	M12
Wide Dynamic Range	Digital WDR
BLC	Yes
HLC	Yes
Defog	Yes
Digital NR	3D DNR
Angle Adjustment	Pan: 0°~360°; Tilt:0°~80°; Rotation: 0°~360°
Image	
Video Compression	Main stream: H.265+/ H.265 / H.264+ / H.264 Sub stream/Third stream: H.265+/ H.265 / H.264+ / H.264/ MJPEG Fourth stream/Fifth stream: H.265 / H.264 / MJPEG
H.264 Compression Standard	Baseline Profile/Main Profile/High Profile
Resolution	4MP (2688×1520),2K (2560×1440), 3MP(2304×1296),1080P (1920×1080), 720P (1280×720), D1, VGA (640 ×480), CIF, 480×240

Ordering Information

PAR-P4TXIRL28NH-AI: 4 Megapixel Turret, 2.8mm Fixed Lens

Main Stream	4MP/2K/3MP/1080P (60Hz : 1 ~ 30fps; 50Hz: 1~25fps)										
Sub Stream	1080P/720P/D1 (60Hz : 1 ~ 30fps; 50Hz: 1~25fps)										
Third Stream	720P/D1/VGA/CIF/480×240 (60Hz : 1 ~ 30fps; 50Hz: 1~25fps)										
Fourth Stream	D1/VGA/CIF/480×240 (60Hz : 1 ~ 30fps; 50Hz: 1~25fps)										
Fifth Stream	D1/VGA/CIF/480×240 (60Hz : 1 ~ 30fps; 50Hz: 1~25fps)										
Bit Rate	64 Kbps ~ 8 Mbps										
Bit Rate Type	VBR / CBR										
Audio Compression	G711A / U										
Image Settings	ROI, Saturation, Brightness, Hue, Contrast,Wide Dynamic, Sharpness, Image Flip, Image Mirror, NR, etc. adjustable through client software or web browser										
ROI	Each ROI to be configured separately										
Interfaces											
Network	RJ 45										
Video Output	No										
Audio	1CH audio input; 1CH audio output; 1CH built-in microphone										
Storage	Built-in micro SD card slot; up to 1 TB										
Reset	Yes										
Alarm	1CH alarm input; 1CH alarm output										
Intelligent Analytics											
Smart Event	Line crossing, region intrusion/entrance/exiting (human/vehicle classification), abandoned/ missing object detection, crowd density detection										
Statistics	Target counting by line, heat map										
Exception Detection	Scene change, video blur and abnormal color detection										
Face Detection	Face detection and face capture										
Video Metadata	Simultaneously captures human body, motor vehicle and non-motor vehicle and extracts 13 human features, 5 motor vehicle features and 1 non-motor vehicle feature										
DORI Distance											
DORI Distance	<table border="1"> <thead> <tr> <th>Lens</th> <th>Detect (ft)</th> <th>Observe (ft)</th> <th>Recognize (ft)</th> <th>Identify (ft)</th> </tr> </thead> <tbody> <tr> <td>2.8mm</td> <td>170 (52m)</td> <td>68 (21m)</td> <td>33 (10m)</td> <td>17 (5m)</td> </tr> </tbody> </table>	Lens	Detect (ft)	Observe (ft)	Recognize (ft)	Identify (ft)	2.8mm	170 (52m)	68 (21m)	33 (10m)	17 (5m)
Lens	Detect (ft)	Observe (ft)	Recognize (ft)	Identify (ft)							
2.8mm	170 (52m)	68 (21m)	33 (10m)	17 (5m)							
Functions											
Remote Monitoring	Web Client/TVT NVR/NVMS/mobile APP										
Web Browser	IE11(plugin-in required)/Chrome 92.0+/Edge 92.0+/Firefox 91.0+/Safari 13.1+										
Online Connection	Support simultaneous monitoring for up to 3 users; Support multi-stream real time transmission										
Network Protocol	UDP, IPv4, IPv6, DHCP, NTP, RTSP, RTP, RTCP, RTMP, FTP, PPPoE, DDNS, SMTP, SNMP, HTTP, 802.1x, UPnP, HTTPS, HTTP POST, QoS										
Interface Protocol	ONVIF										
Storage	Network remote storage; micro SD card storage										
Smart Alarm	Motion detection, sensor alarm, SD card error, SD card full, IP address conflict, cable disconnection										
General Function	Watermark, video mask, heartbeat, image distortion correction, corridor pattern										
Security	Video encryption, firmware encryption, HTTPs encryption, configuration encryption, illegal login lock, IP address filtering, 802.1x authentication, basic and digest authentication for HTTP										
PoE	Yes , IEEE802.3af										
White Light Range	Up to 98' (30 m)										
Ingress Protection	IP 67										
Others											
Power Supply	DC12V/PoE										
Power Consumption	< 5.5W										
Storage Conditions	-22°F~149°F (- 30 °C ~ 65°C), Humidity: less than 95 % (non-condensing)										
Operating Conditions	-22°F~140°F (- 30 °C ~ 60 °C), Humidity: less than 95 % (non-condensing)										
Dimensions	Φ 4.4 x 3.9 in (Φ 111.6 × 99.6 mm)										
Weight (net)	Approx. 1.4lbs (0.623KG)										
Installation	Ceiling mounting; Wall mounting										
Certificate	CE, FCC										
Environmental Protection	Directive EU RoHS, WEEE(2012/19/EU) , directive 94/62/EC and REACH(EC1907/2006)										

