




## PAR-P4TXIRL28NH-AI2

4 Megapixel IP Plug & Play, Outdoor Turret, 24/7 Full-Color Day AND Night, True AI, Fixed lens, Audio Input: Built-in Mic, Audio Output, SD Card Slot, 12VDC/PoE, Superior Starlight

### Features

- True AI Human & Vehicle Classification for Line Crossing, Intrusion Detection, & Other AI Features
- 24/7 Full-Color Day & Night with InVid Tech Illuminate, 0.0001 Lux
- True P2P Connectivity with QR Code Connect NAT 2.0
- 4 Megapixel Resolution
- Supports 2nd Level Video Meta Data
- Cloud Upgradable
- H.265+ / H.265 / H.264+ / H.264
- 30 FPS Recording and Live
- SD Slot For Local Storage: Up to 1TB
- Audio Input: Built-in Mic
- Audio Output
- IP67 Weatherproof
- 12VDC/PoE Operation
- ONVIF
- Free iOS & Android Apps for Smart Phones & Tablets
- Free Central Management Software (CMS) for PC/MAC
- NDAA Compliant



Here is an example of some real camera footage from the InVid Tech Illuminate Series. You can find a video of this on our website. This is real footage with very minimal light. Notice all the colors! The iPhone footage shows how dark the area was. And you can see the difference of a standard IR camera vs InVid Tech Illuminate!

Lens Mount	M12
Wide Dynamic Range	120dB (the next version will support)
BLC	Yes
HLC	Yes
Defog	Yes
Digital NR	3D DNR
EIS	Yes
Angle Adjustment	Pan: 0°~360°; Tilt: 0°~80°; Rotation: 0°~360°
Image	
Video Compression	Main stream: H.265+ / H.265 / H.264+ / H.264 Sub stream/Third stream: H.265+/H.265 / H.264+ / H.264 / MJPEG
H.264 Compression Standard	Baseline Profile/Main Profile/High Profile
Resolution	4MP (2688×1520), 2K (2560×1440), 1080P (1920×1080), 720P (1280×720), D1, VGA (640×480), 640×360, CIF, 480×240
Main Stream	4MP/2K/1080P (60Hz: 1~30fps; 50Hz: 1~25fps)
Sub Stream	720P/D1/640×360/VGA/CIF/480×240 (60Hz: 1~30fps; 50Hz: 1~25fps)
Third Stream	720P/D1/640×360/VGA/CIF/480×240 (60Hz: 1~30fps; 50Hz: 1~25fps)
Bit Rate	32 Kbps ~8 Mbps
Bit Rate Type	VBR / CBR
Audio Compression	G711A / U
Image Settings	ROI, Saturation, Brightness, Hue, Contrast, Wide Dynamic, Sharpness, Image Flip, Image Mirror, NR, etc. adjustable through client software or web browser
ROI	Each ROI to be configured separately
Interfaces	
Network	RJ 45 (10/100 Base-T)
Video Output	No
Audio	1CH audio input; 1CH built-in microphone
Storage	Built-in micro SD card slot; up to 512GB
Reset	Yes
Alarm	No
Intelligent Analytics	
Smart Event	Line crossing, region intrusion/entrance/exiting (human/vehicle classification), abandoned/ missing object detection
Statistics	Target counting by line (human/vehicle classification)
Exception Detection	Scene change, video blur and abnormal color detection, audio exception
Face Detection	Face detection, face capture
DORI Distance	
Lens	2.8mm
2.8mm	170ft (52m) 68ft (21m) 33ft (10m) 17ft (5m)
Functions	
Remote Monitoring	IE browser/ NVR / Paramont CMS / Paramont CMS APP
Web Browser	Chrome 92.0+/Edge 92.0+/Firefox 91.0+/Safari 13.1+
Online Connection	Support simultaneous monitoring for up to 10 users; Support multi-stream real time transmission
Network Protocol	UDP, IPv4, IPv6, DHCP, NTP, RTSP, RTP, RTCP, RTMP, FTP, PPPoE, DDNS, SMTP, SNMP, HTTP, 802.1x, UPnP, HTTPS, HTTP POST, P2P, QoS
Interface Protocol	ONVIF (Profile G/S/T/M)
API & SDK	Yes
Storage	Network remote storage; micro SD card storage
Smart Alarm	Motion detection, SMD, SD card error, SD card full, IP address conflict, Network disconnection
General Function	Watermark, video mask, heartbeat, image distortion correction, corridor pattern, ANR, cloud upgrade, disarming
Security	Video encryption, firmware encryption, HTTPS encryption, configuration encryption, illegal login lock, IP address filtering, 802.1x authentication, basic and token authentication for HTTP/RTSP
PoE	Yes , IEEE802.3af
White Light Range	98'
Ingress Protection	IP 67
Others	
Power Supply	DC12V/PoE
Power Consumption	< 6.5W
Storage Conditions	-22°F~149°F (-30 °C ~ 65°C), Humidity: less than 95 % (non-condensing)
Operating Conditions	-22°F~140°F (-30 °C ~ 60 °C), Humidity: less than 95 % (non-condensing)
Dimensions	Ø4.4 x 3.9 in (Ø 111.6 x 99.6mm)
Weight ( net )	Approx. 1.4 lbs (0.616kg)
Installation	Ceiling mounting; Wall mounting
Certificate	CE, FCC
Environmental Protection	Directive EU RoHS, WEEE(2012/19/EU) , directive 94/62/EC and REACH(EC1907/2006)

Model	PAR-P4TXIRL28NH-AI2
Camera	
Image Sensor	1 / 1.79 "CMOS
Image Size	2688 × 1520
Electronic Shutter	Auto or manual mode; manual mode: 1 / 3s ~ 1 / 100000s
Iris Type	Fixed Iris
Min. Illumination	0.0001 lux @F1.0, AGC ON; 0 lux with illumination on
S/N Ratio	≥50dB
Lens	2.8 mm@F1.0, H.FoV: 112°, V.FoV: 61°, D.FoV: 132°
Focus	Fixed

### Ordering Information

**PAR-P4TXIRL28NH-AI2:** 4 Megapixel Turret, 2.8mm

InVid Tech, reserves the right to make changes to improve our products at any time without notice; we are not responsible for misprints.

