



PAR-P5UFO28NH-AI

5 Megapixel IP, Low Profile, Indoor, Fixed Lens, True AI, IR Range up to 65', True WDR, Built-in Mic, Micro SD Slot, 12VDC/PoE

Features

- True AI Human and Vehicle Classification for Line Crossing and Intrusion Detection
- 5 Megapixel Resolution
- Fixed Lens
- Facial Recognition Capable with Compatible NVR
- True Day/Night with IR Range up to 65'
- H.265+, H.265, H.264+, H.264, MJPEG Compression
- 30 FPS Recording and Live
- True WDR 120dB
- Micro SD Slot: Up to 256GB
- Audio Input: Built-in Mic
- 12VDC/PoE Operation
- ONVIF
- Supports Corridor Mode
- Supports Native Chrome/EDGE Use
- Free iOS & Android Apps for Smart Phones & Tablets
- Free Central Management Software (CMS)
- Free MAC Client
- NDAA Compliant

Camera	PAR-P5UFO28NH-AI
Image Sensor	1 / 2.7 "CMOS
Image Size	2592 × 1944
Electronic Shutter	1 s ~ 1 / 100000 s
Iris Type	Fixed Iris
Min. Illumination	0.02 lux@F1.6,AGC ON; 0 lux with IR
Lens	2.8 mm@F1.6, horizontal FoV: 98.5°; vertical FoV: 82.1°; diagonal FoV:110.9°
Focus	Fixed
Lens Mount	M12
Day & Night	ICR
Wide Dynamic Range	120dB
BLC	Yes
HLC	Yes
Defog	Yes
Digital NR	3D DNR
Angle Adjustment	Pan: 0°~360°; Tilt:0°~70°; Rotation: 0°~350°
Image	
Video Compression	H.265+ / H.265 / H.264+ / H.264 / MJPEG
H.264 Compression Standard	Baseline Profile/Main Profile/High Profile
Resolution	5MP (2592×1944), 4MP (2592×1520), 2K (2560×1440), 3MP (2304×1296),1080P (1920×1080), 720P (1280×720), D1, CIF, 480×240
Main Stream	5MP/4MP/2K/3MP/1080P / 720P(60Hz : 1 ~ 30fps; 50Hz: 1~25fps) HFR mode: 1080P / 720P(60Hz : 1 ~ 60fps; 50Hz: 1~50fps)
Sub Stream	720P/D1/CIF (60Hz : 1 ~ 30fps; 50Hz: 1~25fps)
Third Stream	D1/CIF/480×240 (60Hz : 1 ~ 30fps; 50Hz: 1~25fps)
Bit Rate	64 Kbps ~ 8 Mbps
Bit Rate Type	VBR / CBR
Audio Compression	G711A / U
Image Settings	ROI, Saturation, Brightness, Hue, Contrast,Wide Dynamic, Sharpness, NR, etc. adjustable through client software or web browser
ROI	Each ROI to be configured separately
Interfaces	
Network	RJ45
Video Output	No
Audio	1CH audio input; 1 CH built-in MIC
Storage	Built-in micro SD card slot; up to 256GB
Reset	Yes
Alarm	No
Audio Sensitivity	-36db
Intelligent Analytics (Smart Events)	
Perimeter Protection	Line crossing, intrusion (human/motor vehicle/non-motor vehicle classification)
Target Counting	Line crossing human/motor vehicle/non-motor vehicle counting
Exception Detection	Scene change, video blur and video color cast detection
Functions	
Remote Monitoring	Web browsing,CMS remote control
Online Connection	Support simultaneous monitoring for up to 10 users; Support multi-stream real time transmission
Network Protocol	UDP, IPv4, IPv6, DHCP, NTP, RTSP, RTP, RTCP, ICMP, IGMP, PPPoE, DDNS, SMTP, FTP, SNMP,HTTP, 802.1x, UPnP, HTTPs, QoS
Interface Protocol	ONVIF (Profile T)
Storage	Network remote storage; micro SD card storage
Smart Alarm	Motion detection, SD card error, SD card full
General Function	Watermark, IP address filtering, video mask, heartbeat, illegal login lock, image distortion correction
PoE	Yes , IEEE802.3af
IR Distance	65' (20 m)
Ingress Protection	Indoor
Others	
Power Supply	DC12V/PoE
Power Consumption	< 6W
Operating Environment	-22°F ~ 140°F (- 30 °C ~ 60 °C) Humidity: less than 95 % (non-condensing)
Certifications	UL: E496771
Dimensions	Ø 4.3 x 2.4 in (110 × 59.8mm)
Weight (net)	Approx. .84lbs (0.38KG)
Installation	Ceiling mounting; Wall mounting

Ordering Information

PAR-P5UFO28NH-AI: 5 Megapixel, 2.8mm