



PAR-P6PIR37NH

6 Megapixel IP Plug & Play, Indoor Covert PIR Housing, 3.7mm Fixed Pinhole Lens, IR, Built-in Mic, 12VDC/PoE

Key Features

- Line Crossing & Intrusion Detection with Human/Vehicle Filtering

Core Features

- 6 Megapixel
- Fixed 3.7mm
- Built-in Mic
- True Day/Night with IR Range up to 49'
- IP65 Weather Resistant
- ONVIF
- 12VDC/PoE Operation
- Supports Native Chrome/Edge Use
- Free iOS & Android Apps for Smart Phones & Tablets
- Free Central Management Software (CMS) for PC/MAC
- NDAA Compliant

Model	PAR-P6PIR37NH
Camera	
Image Sensor	1/3" GC4653 CMOS
Soc Chip	Sigmastar SSC377D
Effective Pixels	3072(H)×2048 (V)
Exposure Shutter	AUTO/Manual: 1/10s ~ 1/8000s, Max. Shutter speed adjustable
Day/Night	Auto(Active/passive/schedule)/Day/Night, switch threshold, sensitivity
Image Adjust	Brightness,Saturation,Sharpness,Contrast,Denoise (0-100%) adjustable
White Balance	AWB/MWB
DNR	2D/3D DNR
Encode	
Video Standard	H.264/H.265
Video Resolution	Main Stream: 25fps@6MP(3072x2048),30fps@5MP (2592x1944) / 4MP(2560x1440) / 3MP(2304x1296) / 1080P/720P Sub stream: 10fps@720P, 30fps@D1 (704x576) / (720x480) / VGA (640x480) / QVGA (640x360)
Video Bitrates	Main stream: 64kbps-8Mbps Sub stream: 64kbps-2048kbps VBR/CBR , quality(1-9), GOP(1-128)
Image Rotation	0 / 90 / 180 / 270 degree adjustable
Border Crop	X crop, Y crop
Image Mirror	horizon / vertical / horizon & vertical adjustable
OSD Overlay	Font size(1-4), position, Time, Title, AM/PM, Color, User OSD, Alarm OSD
Privacy Mask	4 areas
Region of Interest	ROI: Each stream support 8 areas
Audio Standard	G.711-u/G.711-a/AAC/PCM, AEC
Built-in Mic	Yes
IR Led	
IR Led	12xΦ5 IR Leds
IR Distance	32 - 49 ft (10-15 M)
Lens	
Focal length	3.7mm MP Pinhole lens
Smart Detection	
Motion Detection	Yes
Perimeter protection (Line Crossing + Intrusion)	Supported. Human + Vehicle Detection Only
Target Detection Type	Human Shape, vehicle
Trigger Action Linkage	Snapshot, Record, Email, FTP
Simultaneous Detection	Maximum 16 targets simultaneous detection
Storage Type	Schedule/Trigger: Email, FTP, NAS
Network Services	
Protocol	HTTP(s)/RTSP/FTP/SMTP/DHCP/NTP/DST/RTP/RTMP/P2P/HiK/IPv4/IPv6/NFS
Web Access	IE, Firefox, Chrome, Edge, Safari, etc.
PC Tool	Windows
ONVIF	23.12 compatible (profile S G T M)
General	
Network Port	1-RJ45, 100Mbps, PoE (IEEE802.3af)
Power Supply	12 VDC/PoE
Power Consumption	< 8 W
Operating Temp.	-4°F ~ 140°F (- 20 °C ~ 60°C), 10%-90%RH
Language	English, simplified Chinese, Chinese Traditional, Japanese, Korean, German, Polish, Italian, Turkish, Ukraine, Russian, etc.
Weight	.33 lbs (.148kg)
Dimensions	4.7 x 2.8 x 1.9 in (120 × 70 × 48mm)

Ordering Information

PAR-P6PIR37NH: 6 Megapixel PIR Camera 3.7mm