



PAR-P8TXIR180NH-AIRBT



8 Megapixel IP Plug & Play, Outdoor Turret, 180° Panoramic View with 2 Stitched Fixed Lenses, up to 98' IR Range, True WDR, White Light up to 65', Red/Blue Flashing Deterrent Light and/or Siren, Built-in Mic/Speaker, SD Card Slot, 12VDC/PoE

Features

- True AI Human & Vehicle Classification for Line Crossing, Intrusion Detection, & Other AI Features
- Red/Blue Flashing Deterrent Light and/or Siren: AI Triggered
- True P2P Connectivity with QR Code Connect NAT 2.0
- Supports Native Chrome/Edge Use
- 8 Megapixel Resolution
- Starlight Illumination
- True Day/Night with IR Range up to 98'
- Supports 2nd Level Video MetaData
- 30 FPS Recording and Live
- Micro SD Slot: Up to 256GB
- Audio Input: Built-in Mic
- Audio Output: Built-in Speaker
- IP66 Weather Resistant
- 12VDC/PoE Operation
- ONVIF
- Cloud Upgradeable
- Free iOS & Android Apps for Smart Phones & Tablets
- Free Central Management Software (CMS) for PC/MAC

Model	PAR-P8TXIR180NH-AIRBT
Camera	
Image Sensor	1 / 2.7 " Progressive Scan CMOS × 2
Max. Resolution	4640×1760
Electronic Shutter	1 / 3 s ~ 1 / 100000 s
Iris Type	Fixed Iris
Min. Illumination	0.0032 lux@F1.6, AGC ON; 0 lux with LED ON
Lens	2.8mm @F1.6
Field of View	Horizontal: 180°; Vertical: 66°
Lens Mount	M12
Day & Night	Auto
Wide Dynamic Range	Digital WDR
BLC	Yes
HLC	Yes
Defog	Yes
S/N Ratio	≥50dB
Digital NR	3D DNR
Angle Adjustment	Pan: 0°~360°; Tilt: 0°~75°; Rotation: 0°~360°
Image	
Video Compression	Main stream: H.265+ / H.265 / H.264+ / H.264 Sub stream: H.265+ / H.265 / H.264+ / H.264 / MJPEG Third stream: H.265+ / H.265 / H.264+ / H.264 / MJPEG
H.264 Compression Standard	Baseline Profile/Main Profile/High Profile
Resolution	8MP (4640×1760), 6MP(3632×1632), 4MP(3200×1200), 2MP (2304×864), 2048×768, 1600×608, 1200×448, 960×368, 640×240
Main Stream	8MP/6MP/4MP/2MP(60Hz : 1~30fps; 50Hz : 1~25fps)
Sub Stream	2048×768/1600×608/1200×448(60Hz:1 ~ 30fps; 50Hz: 1 ~ 25fps)
Third Stream	1200×448/960×368/640×240(60Hz:1 ~ 30fps; 50Hz: 1 ~ 25fps)
Bit Rate	64 Kbps ~10Mbps
Bit Rate Type	VBR / CBR
Audio Compression	G711A / U
Image Settings	ROI, Saturation, Brightness, Hue, Contrast, Wide Dynamic, Sharpness, NR, etc. adjustable through client software or web browser
ROI	Each ROI to be configured separately
Interfaces	
Network	RJ 45 10M/100M self-adaptive Ethernet port
Video Output	No
Audio	1CH audio input; 1CH audio output; 1CH built-in speaker; 2CH built-in MICs
Storage	Built-in micro SD card slot; up to 256GB
Reset	Yes
Alarm	1CH alarm input; 1CH alarm output
Intelligent Analytics	
Smart Event	Line crossing, region intrusion/entrance/exiting (human/vehicle classification), loitering detection, illegal parking detection, abandoned/missing object detection
Statistics	Target counting by line/area, heat map
Exception Detection	Scene change, video blur and abnormal color detection, audio exception
Face Detection	Face detection and face capture
Video Metadata	Simultaneously captures human body, motor vehicle and non-motor vehicle and extracts 13 human features, 4 motor vehicle features and 1 non-motor vehicle feature

DORI Distance	
Lens	Detect Observe Recognize Identify
2.8mm	196ft (60m) 79ft (24m) 39ft (12m) 20ft (6m)
Functions	
Remote Monitoring	Web Browser/Paramont CMS/NVR/Paramont CMS APP
Web Browser	Chrome 89.0+/Edge 89.0+/Firefox 87.0+/Safari 14.0+
Online Connection	Support simultaneous monitoring for up to 10 users; Support multi-stream real time transmission
Network Protocol	UDP, IPv4, IPv6, DHCP, NTP, RTSP, RTP, RTMP, RTCP, PPPoE, DDNS, SMTP, FTP, SNMP, HTTP, HTTP POST, 802.1x, UPnP, HTTPS, P2P, QoS
Interface Protocol	ONVIF Profile G/S/T/M
Storage	Network remote storage; micro SD card storage
Smart Alarm	Motion detection, SMD, SD card error, SD card full, IP address conflict, Network disconnection, sensor alarm, audio alarm, light alarm
General Function	Watermark, video mask, heartbeat, smart supplement light, ANR, cloud upgrade
Security	Video encryption, firmware encryption, HTTPS encryption, configuration encryption, illegal login lock, IP address filtering, 802.1x authentication, basic and token authentication for HTTP/RTSP
PoE	Yes , IEEE802.3af
Supplement Light Range	IR Range: up to 98'; White light range: up to 65'
Ingress Protection	IP66
Others	
Power Supply	DC12V/PoE
Power Consumption	PoE: max. 10.2W; DC12V: max. 9W
Storage Conditions	-22°F~149°F (- 30 °C ~ 65°C), Humidity: less than 95 % (non-condensing)
Operating Conditions	-22°F~140°F (- 30 °C ~ 60 °C), Humidity: less than 95 % (non-condensing)
Dimensions	Ø4.4 x 4 (Ø 111.5 × 102.2mm)
Weight (net)	Approx. 1.6 lbs (0.719KG)
Installation	Ceiling mounting; Wall mounting
Certificate	CE, FCC
Environmental Protection	Directive EU RoHS, WEEE(2012/19/EU) , directive 94/62/EC and REACH(EC1907/2006)



Ordering Information

PAR-P8TXIR180NH-AIRBT 8 Megapixel Turret, 2.8mm

InVid Tech, reserves the right to make changes to improve our products at any time without notice; we are not responsible for misprints.