



PN3A-16X16FNH2

32 Ch NVR with 16 Plug & Play Ports, True Facial Recognition, 320 Mbps, (2) NIC Cards, 4 HD Bays, 4K, with AccuSearch

Features

- 16 Plug & Play Ports for easy camera setup PoE (Power Over Ethernet) available on all ports
- Up to 16 Megapixel Resolution Recording
- (2) NIC Cards: Connect Cameras 1-16 via PnP into unit. Connect cameras 17-32 via switch behind closed network
- Supports Facial Recognition on up to 6 channels, or 3 channels when AccuSearch is enabled
- 320 Mbps Bit Rate Input
- Supports up to 16 channel simultaneous playback
- Works with ONVIF or other supported IP cameras
- Multiple video search options including Analytic and Thumbnail Search for quick retrieval of footage
- AccuSearch: One-click targeted search by matching appearance details across all recordings
- Outputs - 1 HDMI (4K), 1 HDMI (1080p), VGA (1080p)
- True P2P Connectivity with QR Code Connect
- Cloud Upgradeable
- Free iOS & Android Apps for Smart Phones & Tablets
- Free Central Management Software (CMS) for PC/MAC

System	
OS	Embedded Linux
Video	
Compression	H.265S/H.265+/H.265/H.264
IP Video Input	32CH IPC input
Resolution	16MP/12MP/9MP/8MP/6MP/5MP/4MP/3MP/1080P/1280×1024/960P/720P/960H/D1/CIF
Network Bandwidth	320Mbps/320Mbps (incoming/outgoing) *When the AI function of the IPC is enabled, the actual incoming bandwidth(max.bitrate) is more than the set value in the NVR.
Output	HDMI1: 3840 × 2160/1920 × 1080 / 1280 × 1024 / 1024 × 768 HDMI2: 1920 × 1080 / 1280 × 1024 / 1024 × 768 VGA ×1: 1920 × 1080 / 1280 × 1024 / 1024 × 768 VGA and HDMI1 output the same video source
Multi-screen Display	Main output: 1/4/6/8/9/13/16/25/32/36 (live view) AUX output: 1/4/6/8/9 (live view) Max. 32+9CH local live view
Audio	
Network Input	32 CH IPC audio input
2-Way Audio	RCA × 1
Local Output	RCA × 1
Compression	G.711(U/A)
Record	
Record Stream	Dual stream recording
Resolution	16MP/12MP/9MP/8MP/6MP/5MP/4MP/3MP/1080P/1280×1024/960P/720P/960H/D1/CIF
Frame Rate	NTSC: 30fps; PAL: 25fps
Playback	
Simultaneous Playback	Max 16CH
Search	Time slice / time / event / tag / smart search
Smart Search	Highlighted color to display the camera record in a certain period of time, different colors refers to different record events
Function	Play, pause, FF, FB, digital zoom, ACCU-Search, etc.
Decoding Capability	
Live View/ Playback	Non-AI Mode: 1×16MP@30fps/4×8MP@30fps/9×3MP@30fps/16×2MP@30fps AI Mode:1×16MP@30fps/4×6MP@30fps/9×3MP@30fps/16×720P@30fps
Alarm	
Mode	Manual, sensor, motion, exception, smart events, etc.
Input	16 CH local alarm input
Output	4 CH
Triggering	Record, snap, preset, e-mail, etc.

Ordering Information

PN3A-16X16FNH2: 32 Ch, 16 PnP Ports

Face	
Face Detection Performance (AI by IPC)	32CH (PAR-P2FACE/NH-AI Models)
Face Detection Performance (AI by Device ONVIF)	Picture comparison/ACCU-Search disabled: 2 CH(2MP) or 1CH (4MP) Picture comparison/ACCU-Search enabled: 1CH(2MP) or 1CH (4MP)
Face Match Performance	Picture comparison/ACCU-Search disabled: 6 CH Picture comparison/ACCU-Search enabled: 3CH
Comparison Capability	18 pictures / second
Face Picture Database	32 libraries 10000 Face Pictures
Face Picture Search	Search by picture is supported
Database Management	Add, modify, delete and search face pictures
Face Picture Adding	Add face pictures through APP, WEB and external import
Face Picture Comparison	Support successful face recognition alarm and stranger match alarm
Track	Track display on a map
Statistical Graph of Information	Bar graph
Statistical Mode of Information	Statistics by day, week, month, quarter as well as customized time period
Perimeter Protection	
Human/Vehicle Classification (AI by IPC)	Up to 32CH
Human/Vehicle Classification (AI by Device)	Picture comparison/ACCU-Search disabled: 2 CH(2MP) or 1CH (4MP) Picture comparison/ACCU-Search enabled: 1CH(2MP) or 1CH (4MP)
Video Metadata	
Human/Vehicle Attribute Analysis (AI by IPC)	Yes
ACCU-Search	
Video Metadata enable	Attribute ACCU-Search including posture, height, behaviors etc
Face Detection enabled	Face specific ACCU-Search. Not specifically as accurate as facial recognition but will be looking for those faces detected (based on clarity of snapped photo), not attributes
Other Functions	
Fisheye	Supports fisheye dewarping via Web Client and mobile APP (No Local Monitor Dewarp)
Plate Recognition (AI by IPC)	Yes
Network	
Interface	RJ 45 1000 Mbps × 2
Protocol	TCP / IP, HTTP, HTTPS, 802.1X, FTP, DHCP, DDNS, RTP, RTSP, RTCP, NTP, UPnP, SMTP, IPv6, IPv4, UDP, WebSocket, PPPoE, SNMP, IGMP
Client Connection	Max. 128 users access
PoE	
PoE Port	RJ 45 100Mbps × 16
Standard	IEEE802.3AF/AT
Output Power	≤ 150W
Mobile Device	
OS	iOS, Andriod (Paramont CMS app)
Storage	
HDD Interface	SATA × 4, max 26TB for each HDD
E-SATA Interface	E-SATA × 1 (Max Single Drive, up to 26TB, For recording only)
Backup	
Local Backup	USB, USB To HDD (Max 1TB)
Network Backup	Yes
External Interface	
RS 485	Yes (full-duplex) connect to PTZ
USB	USB 3.0 × 1; USB 2.0 × 2
Remote Controller	Included
Others	
Power Supply	ATX 300W(PoE)
Consumption	≤ 20W (without HDD and PoE power supply)
Certificate	CE, FCC
Environmental Protection	Complies with Directive EU RoHS, REACH and WEEE
Dimensions(mm)	17.3 × 15.4 × 2.8 in (440 × 390 × 70 mm)
Working Environment	14°F ~ 122°F (-10°C ~ 50°C) 10% ~90% humidity
Environmental Protection	Complies with Directive EU RoHS, REACH and WEEE

