



PAR-ALL5BIRA27135D

5-2 Megapixel Field Selectable TVI/AHD/CVI/CVBS, Outdoor Long Range Bullet, Motorized AF 2.7-13.5mm Lens, 197' IR Range, True WDR, Dual Voltage

Features

- 5-2 Megapixel Field Selectable**, Sony Sensor and Fuhan 4K DSP
- All-in-One Technology (TVI/AHD/CVI/Analog 960h)
- Motorized AF 2.7-13.5mm Lens
- True Day/Night
- True WDR
- 197' Smart IR Range
- Built-in OSD Board, Built-in Dip Switch, Built-in Optional Video Output
- Up The Cable (UTC) Function
- IP67 Weatherproof
- Dual Voltage
- Through InVid Tech DVR: Free App, CMS & MAC Client
- NDAA Compliant

*Scale down to other resolutions via camera dip switches & OSD

Camera	
Filter	Removable IR Cut Filter
Image Sensor	1/2.8" 5Mega-pixel Sony CMOS
Pixels	2592(H)*1944(V)
Video Output	TVI:5MP 20/12.5 FPS, 4MP/2MP 30/25 FPS AHD:5MP 20/12.5 FPS, 4 MP / 2MP 30/25 FPS CVI:4MP 30/25 FPS, 2 MP 30/25 FPS CVBS*
Video Output By Default	TVI: 5MP @ 20 FPS AHD:2MP @ 30 FPS CVI: 2MP @ 30 FPS CVBS*
Min Illumination	0Lux(12PCs led ON)
Vertical Frequency	NTSC:60Hz PAL:50Hz
IR Range	197 Feet
S/N Ratio	≥54DB
Lens	Motorized AF 2.7-13.5mm IR Lens
Viewing Angle	Horizontal: 108-27 Degree
White Balance	ATW (PRO default), Gray World Optional
BackLight Compensation	OFF (Default)
Day&Night	Default EXT (B/W, Color, AUTO Optional)
OSD	Support
AUTO Gain Control	ON (Default)
3DNR	AUTO
True WDR	Default OFF (≥120DB)
Auto Exposure Mode	Default GLOBAL
Defog	OFF/ON
General	
Power Supply	Dual Voltage
Power Consumption	DC12V: 870mA (MAX)/AC24V:400Ma(MAX)
IP Rating	IP67
Dimension	11.0"×4.4×3.2" (280×111×81mm)
Weight	2.4lbs (1100g)
Storage Temperature	-22 °F ~ 149 °F (-30 °C ~ 65 °C)
Operating Temperature	-22 °F ~ 122 °F (-30 °C ~ 50 °C)

Ordering Information

PAR-ALL5BIRA27135D: 5 Megapixel Long Range Bullet, Motorized AF 2.7-13.5mm Lens