



PAR-ALLDUALDR17D

2 Megapixel Dual Fixed Lens Outdoor Dome, TVI/AHD/CVI/Analog 960h, 12VDC

Features

- 2 Megapixel Resolution
- All-in-One Technology (TVI/AHD/CVI/Analog 960h)
- 1.7mm Dual Fixed Lens
- Up The Cable (UTC) Function
- IP67 Weatherproof
- IK10 Vandal Resistant
- 12VDC Operation
- Through InVid Tech DVR: Free App, CMS & MAC Client

Model	PAR-ALLDUALDR17D
ISP	
Type	EYENIX EN781 * 2 ea
Image sensor	
Sensor type	1/2.8" SONY STARVIS II 2.4Mega CMOS Sensor (IMX662) * 2 ea
active pixels	1943 (H) × 1097 (V) approx. 2.12 M pixels
Effective pixels	1971 (H) × 1113 (V) approx. 2.18 M pixels
Total pixels	2020 (H) × 1196 (V) approx. 2.40 M pixels
Resolution	1920X1080(1080p@30F/25F) 1280X720(720p@30F/31F) CVBS
Scanning system	Progressive Scan
Min. illumination	DAY : 0.2LUX (AGC MAX, SENS-UP OFF, F2.0) NIGHT : 0.01LUX (AGC MAX, SENS-UP OFF, F2.6)
Video Out	AHD (TVI, CVI, CVBS Selectable)
S/N Ratio	More than 50dB
Lens	1.7mm Fixed Lens * 2ea
Function	
AGC	0 ~ 10 Level Adjustable
Shutter Speed	AUTO /FLK/ MAMUAL(1/60Sec ~ 1/30000Sec)
Brightness	0 ~ 20 Level Adjustable
Sens-UP	OFF/AUTO (x2 ~ x32)
WDR	OFF/ON(LINE/FRAME)LOW/MIDDLE/HIGH
BLC	OFF/ON
HLC	OFF/ON
ACE(D-WDR/ATR-EX)	OFF/ON(LOW/MIDDLE/HIGH)
Privacy Masking	OFF/ON (16 Zone)
DEFOG	OFF/ON(LOW/MIDDLE/HIGH)
Day & Night	Auto(AGC)/COLOR/BW
Smart -IR	0~20 Level Adjustable
White Balance	AUTO(1,700K ~ 11,000K)/AWB1/AWB2/AWC-SET/Manual
DNR	2D+3DNR
Mirror	H-MIRROR/V-MIRROR
Sharpness	0~10 Level Adjustable
GAMMA Correction	0.45 ~ 0.75
Language	ENG / JPN / CHN
Coaxial Communication	HD-Analog(UTC)
Operating temperature	14°F ~ 122°F (-10°C ~ +50°C) (Humidity : 20%RH ~ 86%RH)
Storage temperature	-4°F ~ 140°F (-20°C ~ +60°C) (Humidity : 20%RH ~ 101%RH)
Cable	HD-Analog BNC / DC JACK
Power Source	Dual Voltage

Ordering Information

PAR-ALLDUALDR17D: 2 Megapixel Dual Lens Dome

InVid Tech, reserves the right to make changes to improve our products at any time without notice; we are not responsible for misprints.