



### PAR-ALLTXIR28WL

2 Megapixel TVI/AHD/CVI/Analog 960h, Outdoor Turret, 98' LED Range, D-WDR, 12VDC

#### Features

- 2 Megapixel Resolution
- All-in-One Technology (TVI/AHD/CVI/Analog 960h)
- Fixed Lens
- True Day/Night with LED Range up to 98'
- D-WDR
- IP67 Weatherproof
- 2D/3D DNR (Digital Noise Reduction)
- 12VDC Operation
- Up The Cable (UTC) Function
- Through InVid Tech DVR: Free App, CMS & MAC Client

Model	PAR-ALLTXIR28WL
Camera	
Image Sensor	1 / 2.8" CMOS
Resolution	2 Megapixel
Image Size	1920 x 1080
Video Output	AHD / TVI / CVI / CVBS
Default Video Output	TVI
Image System	PAL / NTSC
Electronic Shutter	Auto
LED Distance	98' (30 m)
Frame Rate	30fps(60Hz); 25fps (50Hz)
Min. Illumination	0 lux (LED ON)
Lens	2.8mm
Lens Mount	M12
S / N Ratio	≥52dB ( AGC OFF )
Ingress Protection	IP 67
Functions	
Function Control	OSD ( UTC Control )
Smart LED	Manual or Auto mode
ICR	NO
Digital WDR	Yes
2D/3D DNR	Yes
AGC	Yes
Global Exposure	Yes
Central Exposure	Yes
Auto White Balance	Yes
BLC	Yes
Front Light Compensation	Yes
Contrast	Yes
Saturation/Color Gain	Yes
Sharpness	Yes
Image Setting	Yes
Defect Correction	Auto
Language	Chinese and English
Angle Adjustment	Pan: 0°~360°; Tilt: 0°~75°; Rotation: 0°~360°
Others	
Power Supply	DC12V ( ± 15% )
Power Consumption	LED OFF : < 1W; LED ON : < 3W
Working Environment	-22°F~ 122°F ( - 30 °C ~ 50 °C), 10 % ~ 90 % (relative humidity)
Dimensions	3.7 x 3.3 in ( 94.6 x 82.8 mm)
Weight ( net )	Approx. .86 lb (0.39KG)

#### Ordering Information

PAR-ALLTXIR28WL: 2 Megapixel Turret, 2.8mm