



OPTIONAL Upgrade

INVID-GLOBALINK: InVid Global Link offers real-time solar charging and battery voltage and trends/historical data that can be accessed remotely (via phone, computer, or other device).

INVID-ISSS-RM-2: 2 Surface mounted RJ45 Outlet, 4 port w/ POE+ / High / Passive POE, and 2 25 foot CAT5 Cable with mating RJ45

Configuration Examples

INVID-ISSS-300W2"

Independent Solar Surveillance Solution. Off-grid Security Solution.

- New Full Metal Enclosures
- MPPT Charge Controller
- Withstand Extreme Weather Conditions
- Battery powered surveillance systems that utilize 100% renewable energy. Ready for rapid, remote deployment and automated operation.
- High-quality construction and components
- The universal mounting system is designed for quick and effortless installation on any existing square or round pole, accommodating poles up to ~16" in diameter or 16" square posts.
- The INVID-ISSS-300W2" comes with a bluetooth enabled battery charger (different from the optional INVID-GLOBALINK device) that can be accessed when it is in range (not remotely) and will give system information.

Model	INVID-ISSS-300W2"
Solar Panels & Regulator	300W Panels MPPT Solar Charge Controller
Battery Capacity	2 x 100Ah Lithium-ion
Dimensions	20" x20"x12" Control Enclosure 40" W Solar Panel 73.5" Tall Frame
Weight	200lbs
Construction	Lockable, Industrial-grade, weatherproof steel enclosure. Fits up to 14" mounting pole
Cameras & Recording Sold Separately	Multiple configurations available. Dome, PTZ, or Bullet Cameras 4G Cellular Connectivity Options Live Remote Viewing or Stored Data Options

Ordering Information

INVID-ISSS-300W2": Independent Surveillance System

