




ULT-P2CRBNH

2 Megapixel IP Cylinder Bullet Camera

Features

- 2 Megapixel Resolution
- True Day/Night
- H.264, MJPEG
- 30 FPS Recording and Live
- WDR
- SD Slot for Local Storage: up to 512GB
- IP66 Weather Resistant
- 12VDC/PoE Operation
- ONVIF
- Free iOS & Android Apps for Smart Phones & Tablets
- Free Central Management Software (CMS)
- Free MAC Client



Specification	ULT-P2CRBNH
Image	
Image Sensor	Sony Starvis 2.07Mega Pixels Image Sensor
Size	1/2.8 inch
Scan method	Progressive Scan
Total Pixels	1945(H) x 1109(V), 2.16 Mega Pixels
Effective Pixels	1945(H)x 1097(V), 2.13 Mega Pixels
Camera Web Control	
	Auto(1/30~1/30000), (ANTI-SAT_ON / AE SPEED)
Exposure	AGC (0~10)
	Sens-up (OFF.x2.x4.x8.x16.x32)
Low Illumination	0.05Lux / Sen-up :0.005Lux
Day & Night	AUTO / AUTO-Ext / PRESET / MANUAL
Backlight Comp.	HLC / BLC
Motion Detection	OFF / ON
D N R	2DNR, 3DNR - HDR
Image adjust.	SHARPNESS/DEFOG/SHADING/PRIVACY
	GAMMMMA / MIRROR ,FLIP
White Balance	Auto(indoor) / Auto(Outdoor) / Push/ User
Output Set	Real WDR (15fps WDR on / WDR Off)
	3DNR LEVEL (LOW / MIDDLE / HIGH)
System	Camera Title / Language
Camera RTC	SNTP Enable (ON /OFF)
Storage	Max. 512 GB (Built-in Card Slot)
Lens	
Focal Length	3.6mm ± 5%
F.O.V.	H87.6° x V46.4° x D104.5°
Physical Spec	
Dimension	Ø21.5 x 95.5
Bracket Holder	Ring Type : Option
System	
OS	Embedded Linux
Network	
Interface	RJ45 10/100 Base-T PoE
Protocol	TCP/IP, UDP/IP, DHCP, AUTO IP, JGMP, ICMP, HTTP, UPnP, FTP, SMTP, SNTP, DNx, RTSP, RTMP
Onvif	The latest one
Simultaneous Access	Max. 4 user
Compress Format	H.264 / MJPEG
Resolution	1920x1080 (Full HD) / 1920x720 (HD)
	800x600 (SVGA) / 640x480(VGA) /
	320x240 (QVGA)
Max. Frame Rate	H.264 1080p@30fps + VGA@30fps
Video Streaming	Simultaneously H.264 and MJPEG
	Independent Frame Rate and Bandwidth Control, VBR/CBR Mode
Client Software	Built-in Web, ONVIF (gSOAP, profile S: Spec2.4)
uSD Card	SDIO 3.0
Power	
Power Input	DC12V, PoE (IEEE802.3af)
Consumption	DC12V(1.8W)
Operation Temp./Storage Temp.	14°F ~122°F / -4°F~140°F (-10°C - +50°C / -20°C - +60°C)

Ordering Information

ULT-P2CRBNH: 2 Megapixel IP Cylinder Bullet Camera, 3.6mm