



ULT-P4DRIRN

4 Megapixel IP Plug & Play Mini Rugged Dome, WDR, 90' IR Range, SD Card Slot, PoE/DC12V

Features

- 4 Megapixel (2688 x 1520) Resolution
- Fixed Lens
- H.265+/H.265/H.264+/H.264/MJPEG Compression
- 30 FPS Recording and Live
- True Day/Night
- True WDR 120dB
- 90' IR Range
- IK10 Vandal Resistant
- IP67 Weatherproof
- 12VDC/PoE Operation
- ONVIF
- SD Slot for Local Storage: Up to 128GB
- Free iOS & Android Apps for Smart Phones & Tablets
- Free Central Management Software (CMS) to manage multiple units & sites from a single platform
- Free Mac Client

Model Number	ULT-P4DRIRN
Image Sensor	1/3" progressive scan CMOS
Min. illumination	0.01 lux @ (F1.2, AGC ON), 0 lux with IR
Shutter time	1/3s ~ 1/100,000s
Lens	4mm @ F1.2 2.8mm optional
Angle adjustment	Pan: -90° ~ 90°, tilt 0° ~ 75°, Rotation: 0-355°
Digital noise reduction	3D DNR
Wide dynamic range	True WDR
Day & night	ICR
Video compression	H.264 / H.264+ / MJPEG / H.265 / H.265+
Triple Stream	Yes
Max. image resolution	2688 x 1520
Frame rate	30fps (2688x1520)
Image settings	Saturation, brightness, contrast, sharpness adjustable through client software or web browser
BLC	Yes, zone configurable
On Board Storage	Micro SD slot, up to 128GB
Alarm trigger	Motion detection, tampering alarm
Protocols	TCP/IP, HTTP, DHCP, DNS, DDNS, RTP, RTSP, PPPoE, SMTP, NTP, SNMP, HTTPS, FTP, 802.1x, Qos
System Compatibility	ONVIF, CGI
General functionalities	User authentication, watermark
Communication interface	1 RJ45 10M/ 100 M Ethernet interface
Operating conditions	-22°F ~ 140°F (-30°C ~ 60°C) humidity 90% or less (non-condensing)
Power supply	12 VDC +/- 10%, PoE (802.3af)
Power consumption	Max. 6W
Ratings	IP67 / IK10
IR range	Up to 90ft.
Dimensions	Ø 4.4" x 3.2" (111.7 x 81.28mm)
Weight	1.3 lbs (610g)

Ordering Information

ULT-P4DRIR28N: 4 Megapixel Dome, 2.8mm Lens, White Housing

ULT-P4DRIR4N: 4 Megapixel Dome, 4mm Lens, White Housing

ULT-P4DRIR6N: 4 Megapixel Dome, 6mm Lens, White Housing