



ULT-P4TXIR28WL

4 Megapixel IP Plug & Play, Outdoor Turret, 150' IR Range with White Light Detection, WDR, PoE/12VDC

Features

- 4 Megapixel Resolution
- Fixed Lens
- White Light Detection for Color in Low Light
- True Day/Night with IR Range up to 150'
- H.265+/H.265/H.264+/H.264/MJPEG Compression
- True WDR 120dB
- SD Slot for Local Storage: Up to 128GB
- IP67 Weatherproof
- 12VDC/PoE Operation
- ONVIF
- Free iOS & Android Apps for Smart Phones & Tablets
- Free Central Management Software (CMS)
- Free MAC Client

Model Number	ULT-P4TXIR28WL
Image Sensor	1/2.7 progressive scan CMOS
Min. illumination	0.007 lux @ (F1.2, AGC ON), 0 lux with IR
Shutter time	1/3s ~ 1/100,000s
Lens	2.8mm @ F1.2
Angle adjustment	Pan: 0° ~ 360°, tilt 0° ~ 70°, Rotation: 0 ~ 360
Digital noise reduction	3D DNR
Wide dynamic range	True WDR 120dB
Day & night	ICR
Video compression	H.264 / H.264+ / MJPEG / H.265 / H.265+
Triple stream	Yes
Max. image resolution	2688x1520
Frame rate	30fps (2688x1520)
image settings	Saturation, brightness, contrast, sharpness adjustable through client software or web browser
BLC	Yes
On Board Storage	Micro SD slot, up to 128GB
Alarm trigger	Tampering alarm, network disconnected, IP address conflict, illegal login, HDD full, HDD error"
Protocols	TCP/IP, HTTP, DHCP, DNS, DDNS, RTP, RTSP, PP-PoE, SMTP, NTP, SNMP, HTTPS, FTP, 802.1x, Qos
API	ONVIF(Profile S, Profile G), ISAPI
General functionalities	User authentication, watermark
Communication interface	1 RJ45 10M / 100M Ethernet interface
Operating conditions	-22°F ~ 122°F (-30°C ~ 50°C) humidity 95% or less (non-condensing)
Power supply	12 VDC +/- 10%, PoE (802.3af, class 3)Power consumption
Ratings	IP67
IR range	Up to 150ft
Dimensions	Ø 5.4" x 5"
Weight	1.6lbs
Electrical Box	1.6lbs

Ordering Information

ULT-P4TXIR28WL: 4 Megapixel, 2.8mm

InVid Tech, reserves the right to make changes to improve our products at any time without notice; we are not responsible for misprints.