



ULT-P5BIRM2812

5 Megapixel IP Plug & Play Bullet
2.8-12 Motorized Lens, WDR, 150' IR Range, PoE/DC12V

Features

- 5 Megapixel (2944 x 1656) Resolution
- 2.8-12mm Motorized Varifocal Lens
- H.264/H.264+, MJPEG Compression
- True Day/Night
- True WDR 120dB
- Analog Video Output
- 150' EXIR Range
- Audio Input/Output
- IK10 Vandal Resistant
- IP67 Weatherproof
- 12VDC/PoE Operation
- ONVIF
- Free iOS & Android Apps for Smart Phones & Tablets
- Free Central Management Software (CMS) to manage multiple units & sites from a single platform
- Free Mac Client

Model Number	ULT-P5BIRM2812
Image Sensor	1/2.9 progressive scan CMOS
Min. illumination	0.01 lux @ (F1.2, AGC ON), 0 lux with IR
Shutter time	1/3s ~ 1/100,000s
Lens	2.8 – 12mm @ F1.6
Day & night	IR cut filter with auto switch
Digital noise reduction	3D DNR
Wide dynamic range	120dB
Video compression	H.265+ / H.265 / H.264 / MJPEG / H.264+
Max. Image Resolution	5MP CMOS, 2944 x 1656
Frame rate	20fps (2944x1656), 30fps (2560x1440)
Audio	1/1
BLC	Yes, zone configurable
Network storage	NAS
Alarm	1/1
Protocols	TCP/IP, HTTP, DHCP, DNS, DDNS, RTP, RTSP, PPPoE, SMTP, NTP, SNMP, HTTPS, FTP, 802.1x, QoS
Interoperability	ONVIF, PSIA, CGI
Security	User Authentication, reset button, flickerless, dual stream, heartbeat, mirror, watermark
Communication interface	1 RJ45 10M/ 100 M Ethernet interface
Operating conditions	-30 °C ~ 60 °C (-22 °F ~ 140 °F) humidity 90% or less (non-condensing)
Power supply	12 VDC +/- 10%, PoE (802.3af)
Power consumption	Max, 17.5W
Protection Level	IP67, IK10
IR range	UP to 150ft
Dimension	5.67 x 13.10
Weight	4.17 lbs

Mounting Options



Ordering Information

ULT-P5BIRM2812: 5 Megapixel Motorized 2.8-12mm

*To use these mounts with the selected cameras drill the holes needed into the mount using the diagram included with the camera. InVid Tech. reserves the right to make changes to improve our products at any time without notice; we are not responsible for misprints.