





UN1A-32X16

 $32\ \mathrm{Ch}\ \mathrm{NVR}\ \mathrm{with}\ 16\ \mathrm{Plug}\ \&\ \mathrm{Play}\ \mathrm{Ports}, 256\ \mathrm{Mbps}, 4\ \mathrm{HD}\ \mathrm{Bays}, 4\mathrm{K}$

Features

- 16 Plug & Play Ports for easy camera setup PoE (Power Over Ethernet) available on all ports
- Up to 12 Megapixel Resolution Recording
- 256 Mbps Bit Rate Input
- Supports up to 16 channel simultaneous playback
- Works with ONVIF or other supported IP cameras
- Local HDMI main monitor output with 4K Support
- CVBS Call Monitor Output
- Local VGA main monitor output up to 1080p
- Multiple video search options including Smart and Sub-Period Search for quick retrieval of footage.
- Unique Virtual Host provides remote access to all IPC login menu based features and capabilities
- H.265/H.264/H.264+/MJPEG video compression (H.265 only Supported with Ultra Cameras)
- Free iOS & Android Apps for Smart Phones & Tablets
- Free Central Management Software (CMS) to manage multiple units & sites from a single platform
- Free MAC client software to easily manage your system from your Apple computer

Model Number	UN1A-32X16
Video Compression	H.264 / H.264 / H.265
IP Video Input	32 Ch. (256 Mbps Max input)
Video Output	1 HDMI, 1 VGA, 1 BNC
Audio Input/Output	1/1
Two-way Audio	1/1
Real-time recording resolution	Up to 12 Megapixels
HDMI Output Resolution	4K
VGA Output Resolution	1080P, 60Hz
Synchronous Playback	4 Ch. @ 4K, or 16 Ch. @ 1080P
Alarm Input/ Output	16/4
Network Interface	1 RJ45 10M/100M/1000M adaptive Ethernet Interface
PoE Network Interfac- es/Built-in switch	16 independent 100 Mbps PoE network interfaces
Internal SATA	4 SATA interfaces (up to 14TB each)
eSATA	1 eSATA - Max 8TB HDD. For Recording or Archiving Purposes
USB interface	2 x USB2.0, 1 x USB3.0
Chassis	19-inch rack-mounted 1.5U
Dimensions (W × D × H)	17.5 × 15.4 × 2.75
Power Supply	100 ~ 240 VAC, 20W
Weight	11 lbs (without hard disk)

Ordering Information

UN1A-32X16: 32 Ch NVR with 16 PnP Ports