



## ULT-P4PTZXIT36

4 Megapixel IP PTZ, 36x Zoom, 600' IR Distance, AC24V/High-PoE

### Features

- 4 Megapixel (2560 x 1440) Resolution
- H.265+ / H.265 / H.264+ / H.264 / MJPEG
- True Day/Night
- 36x Optical Zoom
- True WDR
- EXIR Range up to 600'
- CVBS Video Output
- Audio Input/Output
- IP66 Weather Resistant
- Operates to -22° F
- SD Card Local Storage, 128 GB
- 24VAC/High-PoE Power Supply
- Free MAC client software available
- Free iOS & Android Apps for Smart Phones & Tablets
- Free Central Management Software (CMS) to manage multiple units & sites from a single platform

Model Number	ULT-P4PTZXIT36
Image Sensor	1/1.9" Progressive Scan CMOS
Effective Pixel	2560 x 1440
Min. Illumination	Color: 0.005Lux, 0 Lux with IR
White Balance	Auto / Manual/ATW/Indoor/Outdoor/Daylight lamp/sodium lamp
AGC	Auto / Manual
S / N Ratio	>= 55dB
Digital Noise Reduction	3D DNR
Backlight Compensation	BLC
Wide Dynamic Range	True WDR
Shutter Speed	1 ~ 1/30,000s
Day & Night	IR Cut Filter
Digital Zoom	16X
Focus Mode	Auto / Semiautomatic / Manual
Len Focal Length	5.7 mm ~ 205.2 mm, 36X
Zoom Speed	Approx 4.4s (Optical Wide-Tele)
Angle of View	51.1 ~ 1.7 degree (Wide-Tele)
Min. Working Distance	10 ~ 1500 mm (Wide-Tele)
Aperture Range	F1.5 ~ F4.5
Range	Pan: 360° endless; Tilt 20° ~ 90° (Auto Flip)
Speed	Pan Manual Speed: 0.1° ~ 160°/s, Pan Preset speed: 240°/s; Tilt Manual speed: 0.1° ~ 120°/s, Tilt Preset speed: 200°/s
Proportional Zoom	rotation speed can be adjusted automatically according to zoom multiples
Number of Preset	300
Patrol	16 patrols, up to 32 presets per patrol
Park action	Pattern/Pan scan /Tilt scan/Frame scan/Panorama scan/Random scan
Power-off Memory	Support
IR distance	Up to 600ft
IR Intensity	Automatically adjusted, depending on the zoom ratio
Audio input	1 Mic in/Line in interface, line input: 2-2.4V(p-p); output impedance: 1KΩ, ±10%
Audio Output	1 Audio output interface, line level, impedance: 600Ω
Alarm I/O	7/2
Network Ethernet	10Base-T / 100Base-TX, RJ45 connector
Max. Image Resolution	2560 x 1440
Frame Rate	30fps (2560 x 1440)
Image Compression	H.265+ / H.265 / H.264+ / H.264 / MJPEG
Audio Compression	G.711ulaw/G.711alaw/G.726/MP2L2/G.722
Protocols	IPv4/IPv6, HTTP, HTTPS, 802.1x, Qos, FTP, SMTP, UPnP, SNMP, DNS, DDNS, NTP, RTSP, RTP, TCP, UDP, IGMP, ICMP, DHCP, PPPoE
Simultaneous Live View Streams	Up to 20 users Dual Streams
Mini SD Memory Card	Support up to 128GB Micro SD/SDHC/SDXC card. Support Edge recording
User/Host Level	Up to 32 user, 3 Levels: Administrator, Camera control, Live view only
Security Measures	User authentication (ID and PW), Host authentication (MAC address), IP address filtering
Application programming	Open-ended API, support Onvif PSIA and CGI
Web Browser	IE7, IE8, IE9, Chrome 8+, Firefox3.5+, Safari 5+
RS-485 Protocols	Pelco-P, Pelco-D, self-adaptive
Power	Hi-PoE&24 VAC, Max.60W
Operating Temperature	-22°F ~ 149°F (-30°C ~ 65°C)
Humidity	90% or less
Protection Level	IP66 standard TVS 4000V lightning protection, surge protection and voltage transient protection
Dimensions	Φ10.5" x 16.14"
Weight (approx.)	17.64lbs (8kg)

### Ordering Information

**ULT-P4PTZXIT36:** 4 Megapixel IP PTZ, 36x Zoom

*InVid Tech, reserves the right to make changes to improve our products at any time without notice; we are not responsible for misprints.*