



VIS-GIGPOE16-2+

16+2x RJ45+ 2X SFP Gigabit, 19" Rack mountable case, 300W UL Listed

Features

- Conforms to IEEE802.3, IEEE 802.3u, IEEE 802.3ab, IEEE802.3af, IEEE802.3at
- Provides 16 10/100/1000M Base-TX ports and 2 Gigabit RJ-45 Uplink ports
- Provides 16 PoE injector (PoE+) and 300W Built-in power supply
- High back-plane bandwidth 36Gbps
- IEEE802.3x Flow control

Power	
Power Supply	Built-in power supply
Voltage Range	AC100~240V
Consumption	300W for 16 PoE (Each Port 18.75 W)
PoE	IEEE/802.3 AT/AF, Max PoE Capacity: 300W
Ports	1-16 Downlink RJ45 Uplink 2x RJ45 Uplink 2x SFP
Ethernet	
Speed	1-16 Port:10/100/1000Mbps G1:10/100/1000Mbps G2: 10/100/10'00Mbps
Transmission Distance	328ft (100 Meter) For RJ-45 The distance is determined by the optical module The optical module is optional
Network Switch	
Switching capacity	36G
Transfer Rate	14,880 pps for 10Mbps 148,800 pps for 100Mbps 1,488,000 pps for 1000Mbps
MACAddress	4K MAC address table
LINKA/ CT	
On (Green)	The port is connecting
Blinks	The port is receiving or transmitting data
Off	The port is not linked successfully with the device
POE	
On (Green)	PD is connected
Off	No PD is connected or power forwarding fails
PoE pin assignmnet	V+ (Rj45 Pin 1 ,2), V-(Rj45 Pin 3 ,6)
Working Environment	
Working Temperature	32°F ~ 104°F(0°C ~ 40°C)
Storage Temperature	-40°F ~ 158°F (-40°C ~ 70°C)
Humidity Non condensing	0~85%
Mechanical	
Dimension L * W * H	11 x 7.1 x 1.6in (280mm x180mm x 40mm)
Color	Gray
Certification	UL

Ordering Information

VIS-GIGPOE16-2+: 16 Ports Gigabit PoE Ethernet Switch