



## VIS-GIGPOE24-2+

24+2x RJ45+ 2X SFP Full Gigabit, 19" Rack Mountable Case, 400W UL Listed, With 2 Uplink Port

### Features

- Conforms to IEEE802.3, IEEE 802.3u, IEEE 802.3ab, IEEE802.3af, IEEE802.3at
- Provides 24 10/100/1000Base-TX ports and 2 Gigabit Combo Provides 24 PoE injector and 400W Built-in power supply
- High back-plane bandwidth 52Gbps IEEE802.3x Flow control
- EMI standards complies with FCC, CE class B

Power	
Power Supply	Built-in power supply
Voltage Range	AC110V
Consumption	400W for 24 PoE (Each Port 16.6 W)
PoE	IEEE/802.3 AT/AF, Max Capacity: 400W
Ports	1-24 Downlink RJ45 Uplink 2x RJ45 Uplink 2x SFP
Ethernet	
Speed	1~24 Port: 10/100/1000Mbps 25~26: Gigabit Combo
Transmission Distance	328ft (100Meter)for RJ-45 2Km 20Km for SFP Port The optical module is optional
Network Switch	
Switching capacity	52G
Transfer Rate	14,880 pps for 10Mbps 148,800 pps for 100Mbps 1,488,000 pps for 1000Mbps
MACAddress	8K MAC address table
LINKA/ CT	
On (Green)	The port is connecting
Blinks	The port is receiving or transmitting data
Off	The port is not linked successfully with the device
POE	
On (Green)	PD is connected
Off	No PD is connected or power forwarding fails
PoE pin assignmnet	V+ ( Rj45 Pin 1,2), V-( Rj45 Pin 3 ,6)
Working Environment	
Working Temperature	32°F ~ 104°F(0°C ~ 40°C)
Storage Temperature	-40°F ~ 158°F (-40°C ~ 70°C)
Humidity Non condensing	0~90%
Mechanical	
Dimension L * W * H	17.3 x 7.9 x 1.7 in (440mm*200mm*44mm)
Color	Gray
Certification	UL

### Ordering Information

**VIS-GIGPOE24-2+:** 24 Ports Gigabit PoE Ethernet Switch