



VIS-GIGPOE8-2A

8+ 2 xRJ45 Full Gigabit, Max PoE 120w, With 2 Uplink Ports

Features

- Complies with IEEE802.3, IEEE802.3u, IEEE802.3az, IEEE802.3x, IEEE802.3af, IEEE802.3at
- 8-Port 10/100/1000Mbps
- 2-Port 10/100/1000Mbps RJ45 interface for uplink
- Up to 8 IEEE 802.3af devices powered
- Up to 4 IEEE 802.3at devices powered
- Max Single Port up to 30 watts
- Auto detects powered device (PD)
- Circuit protection prevents power interference between ports
- Hardware based 10/100/1000Mbps auto-negotiation and auto MDI/MDI-X
- Desktop size

Model	VIS-GIGPOE8-2A
Ports	8×1000Mbps PoE ports (RJ45)+2×1000Mbps ports(RJ45)
Standards	IEEE802.3, IEEE802.3u, IEEE802.3az, IEEE802.3x, IEEE802.3af, IEEE802.3at
Switching capacity	20Gbps
Forwarding performance	14.88Mpps
Packet Buffer	2Mbit
MAC	2K
Dimensions (W×D×H)	8.7"×5.9"×1.7" (220mm x 150mm x 44mm)
Weight	< 2.73lbs (1.24kg)
Input Voltage	AC: 100-240V, 50/60Hz
MAX. Power	130W
PoE	802.3at/af
Max. PoE Power	Max capacity: 120W Max capacity for single port: 30W
Cooling Fans	1
Operating Temperature	32°F ~ 104°F (0°C ~ 40 °C)
Storage Temperature	-40°F ~ 158°F (-40 °C ~ 70 °C)
Operating Humidity	10% ~ 90% non-condensing
Storage Humidity	5% ~ 90% non-condensing
Indicator	PWR(Green), LNK/ACT(Green), PoE(Orange)
Working Mode	Default (Normal mode): All ports can communicate with each other. VLAN (Secure mode): Downlink ports can communicate only with uplink ports. EXTEND (Surveillance mode): Transmission distance up to 250 meters. Downlink ports can communicate only with uplink ports.

Ordering Information

VIS-GIGPOE8-2A: Gigabit Switch