



## VIS-LRPOE8-2AN

### 8-Port PoE Switch with 2 Uplink Ports

#### Features

- 10 x 100Mbps network ports (RJ45), including 8 PoE ports
- Multiple working modes to address your business needs: Normal, Secure and Surveillance
- Support port traffic control
- Support for secure mode, all downlink ports can communicate only with uplink ports
- Up to 820 ft transmission distance on surveillance mode
- Support buffer optimization
- All metal housing, safe and reliable

Model	VIS-LRPOE8-2AN
Ports	10×100Mbps network ports (RJ45), including 8 PoE ports
Standards	IEEE802.3,IEEE802.3u,IEEE802.3az,IEEE802.3x,IEEE802.3af,IEEE802.3at
Switching capacity	2Gbps
Forwarding performance	1.49Mpps
Packet Buffer	448Kbit
MAC	1K
Dimensions (W×D×H)	6.7 x 4 x 1 in (171*101*25.5mm)
Weight	.64 lb (0.29KG)
Power supply	DC: 48/51V
PoE	802.3at/af (4/5+, 7/8-)
Max. PoE Power	Max capacity: 88W Max capacity for single port: 30W
Prior Ports	1 ~ 2
Cooling Fans	0
Operating temperature	32°F ~ 104°F (0°C-40°C)
Operating humidity	10% ~ 90% (noncondensing)
Storage humidity	5% ~ 90% (noncondensing)
Indicator	POWER: Steady on: AC input is normal Off: No AC input
	No PoE Indicator
	PoE-MAX: Off: The POE power supply power of the whole machine is less than 80% of the specification Steady on: The POE power supply power of the whole machine is greater than 85% of the specification
	LINK/ACT: Off: No link Steady on: Linked Flashing: Transmitting data
Working Mode	Default (Normal mode): All ports can communicate with each other EXTEND (Surveillance mode): Transmission distance up to 250 meters
Certification	UL: A6152, E496771

#### Ordering Information

**VIS-LRPOE8-2AN:** 8-Port PoE Switch with 2 Uplink Ports