



VIS-POE8-2MAN

8-Port Managed PoE Switch

Features

- Web Managed PoE Switch
- Conforms to IEEE802.3, IEEE 802.3u, IEEE 802.3ab
- 8-Port 10/100Mbps supports 50V DC output
- 1-Port 1Gbps Combo + 1-Port 1.25Gbps SFP
- Complies with IEEE 802.3af/802.3at Power over Ethernet
- 125W External power supply
- Auto detects powered device (PD)
- Remote power feeding up to 100m
- Supporting 8K absolute MAC addresses
- High back-plane bandwidth 5.6 Gbps
- Made of metal, desktop and wall mounted

Model	VIS-POE8-2MAN
Power Supply Voltage	External power supply, input DC48~57V
Power Consumption	< 6W
Network Ports	1-8 Port:10/100Mbps G1:Gigabit Combo (RJ-45 10/100/1000Mbps SFP supports optical module rates: 1.25Gbps) G2:SFP supports optical module rates: 1.25Gbps
Transmission Distance	100Meter (328ft) for RJ 45 Transmission distance optional for SFP Port The optical module is optional
Enternet Standard	IEEE 802.3 / 802.3i / 802.3u / 802.3ab / 802.3af/at
Switch Capacity	5.6Gbps
Transfer Rate	14880pps for 10Mbps 148800pps for 100Mbps 1488000pps for 1000Mbps
MAC Address	4K MAC address table
PoE Indicator	Orange light on: PD is connected Orange light off: No PD is connected or power forwarding fails PoE Wattage: Each port≤30W, Whole device<125W
Network Port LED	On Green: The port connection speed is 1000Mbps On Orange: The port connection speed is 10/100Mbps Blinks: The port is receiving or transmitting data Off: The port is not linked successfully with the device
Working Temperature	32°F ~ 104°F (0°C ~ 40°C)
Storage Temperature	-40°F ~ 158°F (-40°C ~ 70°C)
Humidity(non-congeal)	0~85%
Enclosure Dimensions (L*W*H)	8.6 x 4.2 x 1.1 in (218mm×107mm×29mm)
Enclosure Color	Grey or Black
Enclosure Weight	1.5 lbs (700g)

Ordering Information

VIS-POE8-2MAN: 8-Port Managed PoE Switch