



## VIS-P2PTZXIR22NPOE

2 Megapixel IP Plug & Play, Outdoor PTZ, Motorized Auto-Focus, up to 492 IR Range, WDR, Audio Input/Output, SD Card Slot, 12VDC/PoE

### Features

- 2 Megapixel Resolution
- Motorized Auto-Focus 5.2-114.4 Lens
- True Day/Night with IR Range up to 492'
- Ultra H.265,H.265,H.264,MJPEG Compression
- 60 FPS Recording and Live
- True WDR 120dB
- Micro SD Slot: Up to 256GB
- Audio Input
- Audio Output
- IP66 Weather Resistant
- 12VDC/PoE Operation
- ONVIF
- Free iOS & Android Apps for Smart Phones & Tablets
- Free Central Management Software (CMS)
- Free MAC Client

Camera	VIS-P2PTZXIR22NPOE															
Sensor	1/2.8", 2.0 megapixel, progressive scan, CMOS															
Lens	5.2 ~ 114.4mm, AF automatic focusing and motorized zoom lens															
Digital Zoom	16															
Optical Zoom	22															
DORI Distance	<table border="1"> <thead> <tr> <th>Lens(mm)</th> <th>Detect(m)</th> <th>Observe(m)</th> <th>Recognize(m)</th> <th>Identify(m)</th> </tr> </thead> <tbody> <tr> <td>5.2</td> <td>80.7</td> <td>32.3</td> <td>16.1</td> <td>8.1</td> </tr> <tr> <td>114.4</td> <td>1775.2</td> <td>710.1</td> <td>355</td> <td>177.5</td> </tr> </tbody> </table>	Lens(mm)	Detect(m)	Observe(m)	Recognize(m)	Identify(m)	5.2	80.7	32.3	16.1	8.1	114.4	1775.2	710.1	355	177.5
Lens(mm)	Detect(m)	Observe(m)	Recognize(m)	Identify(m)												
5.2	80.7	32.3	16.1	8.1												
114.4	1775.2	710.1	355	177.5												
Angle of View (H)	53.4° ~ 2.7°															
Angle of View (V)	32.3° ~ 1.5°															
Angle of View (O)	60.3° ~ 3.1°															
Shutter	Auto/Manual; shutter time: 1 ~ 1/100000s															
Minimum Illumination	Colour: 0.001 lux (F1.5,AGC ON) 0 lux with IR															
Iris	Auto/Manual; F1.5 ~ F3.8															
Day/Night	IR-cut filter with auto switch (ICR)															
Digital noise reduction	2D/3D DNR															
S/N	>52dB															
IR Range	UP to 150m (492ft)															
Defog	Digital Defog															
WDR	120dB															
Video																
Video Compression	Ultra 265, H.265, H.264, MJPEG															
H.264 code profile	Baseline profile, Main Profile, High Profile															
Frame Rate	Main Stream: 2MP (1920*1080), Max 60fps; Sub Stream: 2MP (1920*1080), Max 60fps; Third Stream: D1 (720*576), Max 60fps															
HLC	Supported															
BLC	Supported															
EIS	Supported															
OSD	Up to 8 OSDs															
Privacy Mask	Up to 24 areas(Up to 8 blacks or 8 mosaic in the same picture)															
ROI	Up to 8 areas															
Motion Detection	Up to 4 areas															
Smart																
General Function	Watermark, IP Address Filtering, Tampering Alarm, Alarm input, Alarm output, Access Policy, ARP Protection, RTSP Authentication, User Authentication															
Audio																
Audio Compression	G.711															
Two-way audio	Supported															
Suppression	Supported															
Sampling Rate	8KHZ															
Storage																
Edge Storage	Micro SD, up to 256GB															
Network Storage	ANR															
Network																
Protocols	IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, PPPoE, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, 802.1x, SNMP, QoS, RTMP															
Compatible Integration	ONVIF (Profile S, Profile G, Profile T), API															
Pan & Tilt																
Pan Range	360° (endless)															
Pan Speed	2°/s ~ 75°/s Preset speed: 180°/s															
Tilt Range																
Tilt Speed	2° ~ 75°/s Preset speed: 80°/s															
Number of Presets	1024															
Patrol	Preset patrol, route patrol, recorded patrol															
Home Position	Supported															
Interface																
Audio I/O	Audio cable 1 Input: impedance 35kΩ; amplitude 2V (p-p) 1 Output: impedance 600Ω; amplitude 2V (p-p)															
Alarm I/O	44197															
Network	1 RJ45 10M/100M Base-TX Ethernet															
General																
Power	DC 12V±10%, PoE (PSE required) Power consumption: 4~27.6W															
Dimensions (Ø x H)	Ø8.7" x 14.5" (Ø220 x 369mm)															
Weight	7.5lb (3.4kg)															
Working Environment	-40°F ~ 149°F (-40°C ~ 65°C), Humidity: ≤95% RH (non-condensing)															
Ingress Resistant	IP66															
Reset Button	Supported															

### Ordering Information

VIS-P2PTZXIR22NPOE: Motorized Auto-Focus, 5.2-114.4mm