



## VIS-P2PTZXIR22POE

2 Megapixel IP, Outdoor PTZ, 22x, 492' EXIR Range, D-WDR, Audio Input/Output, SD Card Slot, PoE+/DC12V With POE Injector

### Features

- 2 Megapixel (1920 x 1080) Resolution
- Ultra H.265/H.265/H.264/MJPEG Compression
- True Day/Night
- Smart Analytics
- ONVIF
- 22x Optical Zoom
- Digital WDR
- Smart EXIR Range up to 492'
- Audio Input/Output
- IP66 Weather Resistant
- Operates to -40° F
- Micro SD Slot: Up to 256GB
- 12VDC/High-PoE Power Supply (Included)
- Free iOS & Android Apps for Smart Phones & Tablets
- Free Central Management Software (CMS) to manage multiple units & sites from a single platform
- Free MAC client software available

### Ordering Information

**VIS-P2PTZXIR22POE:** 2 Megapixel 22x PTZ

Camera	VIS-P2PTZXIR22POE
Sensor	1/2.9" progressive scan, 2.0 megapixel, CMOS
Lens	5.2~ 114.4 mm AF automatic focusing and motorized zoom lens
Digital Zoom	16
Optical Zoom	22
Angle of View (V) DORI Distance	5.2mm: 274' (Detect), 109' (Observe), 55' (Recognize), 28' (Identify)
Angle of View (O) DORI Distance	114.4mm: 6032' (Detect), 2413' (Observe), 1206' (Recognize), 603' (Identify)
Angle of View (H)	54.40°~ 3.44°
Angle of View (V)	39.2° ~1.9°
Angle of View (O)	66.9° ~4.1°
Adjustment angle	Pan: 0°~360°, Tilt: 0°~90°, Rotate: 0°~360°
Shutter	Auto/Manual, shutter time: 1 ~ 1/100000 s
Minimum Illumination	Color: 0.01 lux (F1.5,AGC ON)
0 lux with IR	
Iris	F1.5
Day/Night	IR-cut filter with auto switch (ICR)
Digital noise reduction	2D/3D DNR
S/N	>55 dB
IR Range	UP to 150m (492ft)
Defog	Digital Defog
WDR	DWDR
Video	
Video Compression	Ultra 265,H.265, H.264, MJPEG
H.264 code profile	Baseline profile, Main Profile, High Profile
Frame Rate	Main Stream:2MP (1920x1080):Max. 30 fps; Sub Stream:2MP (1920x1080):Max. 30 fps; Third Stream: D1 (720x576): Max. 30 fps
HLC	Supported
BLC	Supported
EIS	Supported
OSD	Up to 8 OSDs
Privacy Mask	Up to 24 areas
ROI	Up to 8 areas
Motion Detection	Up to 4 areas
Smart	
Behavior Detection	Intrusion, cross line, motion detection
Intrusion	Enter and loiter in a pre-defined virtual region
cross line	Cross a pre-defined virtual line
motion detection	Moving within a pre-defined virtual region
Recognition	Face detection Audio detection
Statistical Analysis	People counting
General Function	Watermark, IP Address Filtering, Tampering Alarm, Alarm input, Alarm output, Access Policy, ARP Protection, RTSP Authentication, User Authentication
Audio	
Audio Compression	G.711
Two-way Audio	Supported
Suppression	Supported
Sampling Rate	8 KHZ
Storage	
Edge Storage	Micro SD, up to 256 GB
Network Storage	ANR
Network	
Protocols	IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, PPPoE, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, 802.1x, SNMP
Compatible Integration	ONVIF(Profile S, Profile G), API
Pan & Tilt	
Pan Range	360°
Pan Speed	0.1°/s ~ 240°/s Preset speed: 300°/s
Tilt Range	-15° ~ +90° (auto reverse)
Tilt Speed	0.1° ~ 80°/s Preset speed: 80°/s
Number of Presets	1024
Patrol	Preset patrol, route patrol, recorded patrol
Home Position	Supported
Interface	
Audio I/O	1 Input: impedance 35 kΩ; amplitude 2 V (p-p) 1 Output: impedance 600 Ω; amplitude 2 V (p-p)
Alarm I/O	1 / 1
Network	1 RJ45 10M/100M Base-TX Ethernet
General	
Power	DC 12V±10%, PoE (PSE Included) Power consumption: 16~30 W
Dimensions (Ø x H)	Φ215mm×344mm(Φ8.5" x13.5")
Weight	3kg(6.6lb)
Working Environment	-40°C ~ +65°C (-40°F ~ 149°F), Humidity:10%~90% RH(non-condensing)
Ingress Protection	IP66
Reset Button	Supported
Certifications	UL Listed