



VIS-DUALDOORBELL

3 Megapixel Front Facing & 2 Megapixel Downward Package Facing Doorbell. Up to 16' IR and 6' White Light Range. Supports audio/video with built-in eMMC card, AC 12~24V

Features

- Dual Lens:
3 Megapixel 2.4mm with 131° View
2 Megapixel 2.4mm with 109° View
- H.265/H.264 Compression
- True WDR
- IR + White Light Support
- Two-way remote communication
- IP65
- 12-24V AC
- Built-in 8GB SD eMMC Storage
- WiFi Supported: 2.4GHz + 5GHz
- Works with Mechanical Chimes
- Free iOS & Android Apps for Smart Phones & Tablets

Model	VIS-DUALDOORBELL
Camera	
Resolution -- main camera	3MP
Resolution -- sub camera	2MP
FOV -- main camera	Horizontal: 116° Vertical: 82.5° Diagonal: 131°
FOV -- sub camera	Horizontal: 96.8° Vertical: 52.6° Diagonal: 109.9°
Power kit	
power kit	240 mAH rechargeable lithium battery (for mechanical chime)
Charge temperature	32°F ~ 113°F (0°C to 45 °C)
Alarm Event	
Motion detection alarm	Support
UMD alarm	Supports human body detection alarm
Package detection alarm	Support

Ordering Information

VIS-DUALDOORBELL: Doorbell Camera

Wi-Fi	
Operating frequency band	2.4 GHz and 5G Hz
BLE function	Compatible, integrated BLE, supports network connection via Bluetooth
Antenna type	Built-in omnidirectional antenna
WLAN	802.11 b/g/n/ax
Encryption	WPA-PSK/WPA2-PSK/WPA3-personal
Bluetooth	Support, integrated in Wi-Fi chip
SUB-1G	
SUB-1G	Supported, for chime connection (VIS-DOORCHIME)
Chimes	Max 3 wireless chimes or 1 mechanical chime
Mechanical Chime Supported	LA11WH-1, C210-W
Interface	
Reset button	1 micro switch for both pairing and reset
Built-in Mic	Support
Built-in speaker	Support
Client	InVid Vision Live, Vision Tools (IP Utility), InVid CMS
Network protocol	TCP/IP, IPv4, HTTP, RTP, RTSP, NTP
Storage	Built-in 8GB eMMC Storage (No additional SD storage)
Illuminator	
Illumination scheme	IR + white light
Illumination distance	IR: 16' (5m) White light: 6' (2m)
Min. Illumination	0.02 lux
General	
Dimensions	2.2 x 6.2 x 1.1 in (55.8 mm x 156.5 mm x 27.9 mm)
Weight	Net weight: .3lbs (142g) Gross weight: .7lbs (295g)
Power consumption	10W
Installation method	With bracket installation, the power cable is installed on the bracket, and the doorbell is connected to the bracket through the contacts.
Button	One call button
Power source	Contact: AC 12V to 24V AC
Operating temperature	-22°F ~ 140°F (-30 °C to 60 °C)
Ingress protection	IP65
WDR	
WDR	Supports DWDR, main camera 80dB, sub camera 58dB
Video	
Video compression	H.265, H.264
Audio	
Audio bit rate	128 Kbps
Audio sampling rate	8K
Audio compression	G711, MP3, PCM
Certification	
Certification	CB, CE LVD, CE EMC, CE RED, FCC SDOC, FCC ID

