



VIS-P5BXIRA2812LC

5 Megapixel IP Plug & Play, Outdoor Bullet, 2.8-12mm Auto-Focus Motorized, 98' EXIR Range, SD Card Slot, PoE/DC12V

Features

- 5 Megapixel (2592 x 1944) Resolution
- Motorized Auto-Focus 2.8-12mm Lens
- Ultra H.265/H.265/H.264/MJPEG Compression
- True Day/Night
- D-WDR
- Cloud Upgradeable
- Smart EXIR Range up to 98'
- Micro SD Slot: Up to 256GB
- IP67 Weather Resistant
- 12VDC/PoE Operation
- ONVIF
- Free iOS & Android Apps for Smart Phones & Tablets
- Free Central Management Software (CMS) to manage multiple units & sites from a single platform
- Free MAC client software available to manage your system from your Apple computer

Camera	VIS-P5BXIRA2812LC
Sensor	1/2.7", 5.0 megapixel, progressive scan, CMOS
Lens	2.8~12 mm, motorized zoom lens
DORI Distance	2.8mm: 206' (Detect), 82' (Observe), 41' (Recognize), 20' (Identify) 12mm: 885' (Detect), 354' (Observe), 177' (Recognize), 88' (Identify)
Angle of View (H)	83.6°~31.5°
Angle of View (V)	58.4°~14.9°
Angle of View (O)	108.7~38.7°
Adjustment angle	Pan: 0°~360°, Tilt: 0°~90°, Rotate: 0°~360°
Shutter	Auto/Manual, 1~1/100000 s
Minimum Illumination	Color: 0.01Lux (F1.8 AGC ON), 0 Lux with IR
Day/Night	IR-cut filter with auto switch (ICR)
Digital noise reduction	2D/3D DNR
S/N	>52dB
IR Range	Up to 30m (98 ft) IR range
WDR	DWDR
Video	
Video Compression	Ultra 265,H.265, H.264,MJPEG
H.264 code profile	Baseline profile, Main Profile, High Profile
Frame Rate	Main Stream:5MP (2592*1944): Max. 15fps;
	Sub Stream: 720P (1280*720): Max. 30 fps;
	Third Stream: D1 (704*576): Max. 30fps
HLC	Supported
BLC	Supported
OSD	Up to 4 OSDs
Privacy Mask	Up to 8 areas
ROI	Up to 2 areas
Motion Detection	Up to 4 areas
Network	
Protocols	IPv4,IGMP,ICMP,ARP,TCP,UDP,DHCP, RTP,RTSP,RTCP,DNS,DDNS,NTP,FTP,UPnP,HTTP,HTTPS,SMTP, SSL
Compatible Integration	ONVIF(Profile S, Profile G), API
Interface	
Network	1 RJ45 100M Base-TX Ethernet
Edge Storage	MicroSD, up to 256GB
General	
Power	DC12V±25%, PoE (IEEE802.3 af) Power consumption: Max 7W
Dimensions (Ø x H)	253.4×86×71.7mm(9.98"×3.4"×2.8")
Weight	1kg (2.2lb)
Working Environment	-30°C ~ +60°C (-22°F ~ 140°F), Humidity :10%~90% RH(non-condensing)
Ingress Protection	IP67

Ordering Information

VIS-P5BXIRA2812LC: 5 Megapixel Auto-Focus Motorized Bullet, 2.8-12mm