



VIS-P5BXIRLC

5 Megapixel IP Plug & Play, Outdoor Bullet, Fixed Lens, 98' EXIR Range, PoE/DC12V

Features

- Smart Analytics-AI Human Body Detection
- 5 Megapixel (2592 x 1944) Resolution
- Fixed Lens
- Ultra H.265/H.265/H.264/MJPEG Compression
- True Day/Night
- D-WDR
- Cloud Upgradeable
- Smart EXIR Range up to 98'
- IP67 Weather Resistant
- 12VDC/PoE Operation
- ONVIF
- Free iOS & Android Apps for Smart Phones & Tablets
- Free Central Management Software (CMS) to manage multiple units & sites from a single platform
- Free MAC client software available to manage your system from your Apple computer

Camera	VIS-P4TXIRNH			
Sensor	1/3", 4.0 megapixel, progressive scan, CMOS			
Lens	2.8mm@F2.0			
DORI Distance	Lens (mm)	Detect (ft)	Observe (ft)	Recognize (ft) Identify (ft)
	4	196.9 (60m)	78.7(24m)	39.4(12m) 19.7(6m)
DORI Distance	6	295.3(90m)	118.1(36m)	59.1(18m) 29.5(9m)
	Angle of view(H)	107.8°		
Angle of View (V)	57.0°			
Angle of View (O)	140.1°			
Adjustment angle	Pan: 0° ~ 360° Tilt: 0° ~ 80° Rotate: 0° ~ 360°			
Shutter	Auto/Manual, 1 ~ 1/100000s			
Minimum Illumination	Colour:0.01Lux (F2.0, AGC ON)			
	0Lux with IR on			
Day/Night	IR-cut filter with auto switch (ICR)			
Digital noise reduction	2D/3D DNR			
S/N	>56dB			
IR Range	Up to 98ft (30m) IR range			
Wavelength	850nm			
IR On/Off Control	Auto/Manual			
Defog	Digital Defog			
WDR	120dB			
Video				
Video Compression	Ultra 265, H.265, H.264, MJPEG			
H.264 code profile	Baseline profile, Main Profile			
Frame Rate	Main Stream: 4MP (2688*1520), Max 30fps; 4MP (2560*1440), Max 30fps; 3MP (2304*1296), Max 30fps; 1080P(1920*1080),Max30fps			
	Sub Stream: 720P (1280*720), Max 30fps;			
	Third Stream: 4CIF (704*576), Max 30fps			
Video Bit Rate	128 Kbps~16 Mbps			
OSD	Up to 4 OSDs			
Privacy Mask	Up to 4 areas			
ROI	Up to 4 areas			
Motion Detection	Up to 4 areas			
Image				
White Balance	Auto/Outdoor/Fine Tune/Sodium Lamp/Locked/Auto2			
Digital noise reduction	2D/3D DNR			
Smart IR	Support			
Flip	Normal/Vertical/Horizontal/180°			
Dewarping	NA			
HLC	Supported			
BLC	Supported			
Audio				
Audio Compression	G.711			
Suppression	Supported			
Sampling Rate	8KHZ			
Storage				
Edge Storage	Micro SD, up to 256 GB			
Network Storage	ANR			
Smart				
Behavior Detection	Intrusion, Human Body Detection, Motion detection, Tampering alarm, Audio Detection			
Network				
Protocols	IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, SSL			
Compatible Integration	ONVIF (Profile S, Profile G, Profile T), API			
Clients	InVid Vision (Mobile App)			
	Vision Tools (IP Utility)			
Web Browser	InVid CMS			
	Plug-in required live view: IE9+, Chrome 41 & below, Firefox 52& below			
Interface	Plug-in free live view: Chrome 57.0+, Firefox 58.0+, Edge 16+, Safari 11+			
Network	1 RJ45 10M/100M Base-TX Ethernet			
Built-in Mic	Supported			
Certifications				
Certifications	CE: EN 60950-1			
	UL: UL60950-1			
	FCC: FCC Part 15			
General				
Power	DC 12V±25%, PoE (IEEE 802.3af)			
	Power consumption: Max 5.5W			
Dimensions (Ø x H)	Φ4.6" x 3.8" (Φ118 x 96mm)			
Net Weight	0.73lb (0.33kg)			
Material	Metal + Plastic			
Operating Conditions	-22°F ~ 140°F (-30°C ~ 60°C), Humidity: ≤95% RH (non-condensing)			
Storage Environment	-22°F ~ 140°F (-30°C ~ 60°C), Humidity: ≤95% RH (non-condensing)			
Surge Protection	2KV			
Ingress Protection	IP67			

Ordering Information

VIS-P5BXIR4LC: 5 Megapixel Bullet, 4mm

VIS-P5BXIR6LC: 5 Megapixel Bullet, 6mm