



VIS-D1A-4

4 Ch +2 Bonus IP Ch, Up to 6 cameras total, TVI/AHD/CVI/Analog/IP
Universal Port Recorder/Encoder, 1 HD Bay

Features

- 4 Channel Universal Port DVR (TVI/AHD/CVI/Analog/IP)
- Supports 5MP for TVI/AHD & 1080p for CVI, CVBS
- 2 Bonus IP Channels - Up to 8 Megapixel
- H.264 Video Compression
- True P2P Connectivity with QR Code Connect
- Simultaneous HDMI/VGA up to 1080p Resolution
- Supports up to 4 Channel Simultaneous Playback
- Multiple video search options including Smart Search for quick retrieval of footage.
- Upgrade your recorder via the Cloud
- Free iOS & Android Apps for Smart Phones & Tablets
- Free Central Management Software (CMS) to manage multiple units & sites from a single platform
- Free MAC client software to easily manage your system from your Apple computer

Model	VIS-D1A-4
Video/Audio Input	
Analog Video Input	4-ch, BNC
IP Video Input	2-ch (only IP up to 6ch)
Supported Analog Camera Types	Support AHD input: 5MP, 4MP, 3MP, 1080P/30 Hz, 1080P/25 Hz, 720P/30 Hz, 720P/25 Hz, Support TVI input: 5MP, 3MP, 1080P/30 Hz, 1080P/25 Hz, 720P/30 Hz, 720P/25 Hz Support CVI input: 1080P/25Hz, 1080P/30Hz, 720P/25Hz, 720P/30Hz Support CVBS input
Audio Input	4-ch, RCA
Two-way Audio Input	1-ch, RCA
Network	
Incoming Bandwidth	40Mbps
Outgoing Bandwidth	40Mbps
Remote Users	128
Protocols	TCP/IP, P2P, UPnP, NTP, DHCP, PPPoE
Video/Audio Output	
HDMI/VGA Output	1920x1080p/60Hz, 1920x1080p/50Hz, 1600x1200/60Hz, 1280x1024/60Hz, 1280x720/60Hz, 1024x768/60Hz
Recording Resolution	5MP/4MP/3MP/1080p/720p/960H/4CIF/CIF/QCIF
Frame Rate	Mainstream: 5MP@10fps/4MP@12fps/3MP@16fps/1080P@25fps/720P@30 ps/960H@30fps, Sub stream: 960H/D1@16fps CIF/QCIF@25fps/30fps
Audio Output	1-ch, RCA
Synchronous Playback	6-ch
Decoding	
Decoding format	H.264
Live View/ Playback	8MP(IP)/5MP/4MP/3MP/1080p/720p/960H/4CIF/CIF/QCIF
Hard Disk	
SATA	1 SATA interface
Capacity	up to 14TB WD/Up to 18TB Seagate
External Interface	
Network Interface	1 RJ45 10M/100M self-adaptive Ethernet Interfaces
Serial Interface	1 x RS485
USB Interface	Rear panel: 1 x USB2.0, Front panel: 1xUSB2.0
General	
Power Supply	12V DC Power Consumption: ≤ 5 W(without HDD)
Working Environment	+14°F ~ +131°F (-10°C ~ + 55°C), Humidity ≤ 90% RH(non-condensing)
Dimensions (W×D×H)	10.2" × 9.4"×1.7" (260mm × 240mm× 44mm)
Weight (without HDD)	2.47 lb (≤ 1.12 Kg)
Certification	UL

Ordering Information

VIS-D1A-4: 4 Ch DVR