



VN1A-32X16

32 Ch NVR with 16 Plug & Play Ports, 320 Mbps, 2 HD Bays, With Cloud Upgrade

Features

- 16 Plug & Play Ports for easy camera setup PoE (Power Over Ethernet) available on all ports
- Up to 12 Megapixel Resolution Recording
- 160 Mbs Bit Rate Input
- Supports up to 16 channel simultaneous playback
- Works with ONVIF or other supported IP cameras
- Local HDMI main monitor output with 4K Support
- Local VGA main monitor output up to 1080p
- EZ Vision Stream Connect for Networking
- Multiple video search options including Smart Search for quick retrieval of footage.
- H.265/H.264 video compression
- Free iOS & Android Apps for Smart Phones & Tablets
- Free Central Management Software (CMS) to manage multiple units & sites from a single platform
- Free MAC client software to easily manage your system from your Apple computer

Model	VN1A-32X16
Video/Audio Input	
IP Video Input	32-ch
Two-way Audio Input	1-ch, RCA
Network	
Incoming Bandwidth	320Mbps
Outgoing Bandwidth	320Mbps
Remote Users	128
Protocols	P2P, UPnP, NTP, DHCP, PPPoE
Video/Audio Output	
HDMI/VGA output	HDMI1/VGA: 1920x1080p /60Hz, 1920x1080p /50Hz, 1600x1200 /60Hz, 1280x1024 /60Hz, 1280x720 /60Hz, 1024x768 /60Hz HDMI2: 4K (3840x2160) /60Hz, 4K (3840x2160) /30Hz, 1920x1080p /60Hz, 1920x1080p /50Hz, 1600x1200 /60Hz, 1280x1024 /60Hz, 1280x720 /60Hz, 1024x768 /60Hz
Recording Resolution	12MP/8MP/6MP/5MP/4MP/3MP/1080p/960p/720p/D1/2CIF/CIF
Audio Output	1-ch, RCA
Synchronous Playback	32-ch
Decoding	
Compression	H.265, H.264
Live view/Playback	12MP/8MP/6MP/5MP/4MP/3MP/1080p/960p/720p/D1/2CIF/CIF
Capability	4 x 12MP@20, 4 x 4K@30, 8x 4MP@20, 16 x 1080p@25, 32 x 720p@25
Hard Disk	
SATA	4 SATA interfaces
Capacity	Max14TB for HDD
External Interface	
Network Interface	1 RJ45 10M/100M/1000M self-adaptive Ethernet Interface
Serial Interface	1 x RS485
USB Interface	Front panel: 2 x USB2.0, Rear panel: 1 x USB3.0
Alarm In	16-ch
Alarm Out	4-ch
Power Output	12 VDC
PoE	
Interface	16 independent 100 Mbps PoE network interfaces
Max Power	Max 30W for single port, Max 200W in total (12.5W for each)
Supported Standard	IEEE 802.3af
General	
Power Supply	100 ~ 240 VAC
Consumption (Without HDD)	≤ 20 W
Working Environment	+14°F ~ +131°F(-10°C ~ +55°C)
Working Humidity	10% ~ 90%
Chassis	Rack Mounted 24 Chassis
Dimensions(W×D×H)	3.4 x 17.4 x 16.7 In (86 x 442 x 425mm)
Weight (without HDD)	≤ 11.55 lb (5.24 Kg)

Ordering Information

VN1A-32X16: 32 Ch NVR with 16 Plug & Play Ports
Available with 1/2/3/4/6/8/10/12/14 TB Hard Drive Options